



## **erwin Data Modeler**

### **Feature Tour**

**Release 12.0**

## Legal Notices

This Documentation, which includes embedded help systems and electronically distributed materials (hereinafter referred to as the “Documentation”), is for your informational purposes only and is subject to change or withdrawal by Quest Software, Inc and/or its affiliates at any time. This Documentation is proprietary information of Quest Software, Inc and/or its affiliates and may not be copied, transferred, reproduced, disclosed, modified or duplicated, in whole or in part, without the prior written consent of Quest Software, Inc and/or its affiliates

If you are a licensed user of the software product(s) addressed in the Documentation, you may print or otherwise make available a reasonable number of copies of the Documentation for internal use by you and your employees in connection with that software, provided that all Quest Software, Inc and/or its affiliates copyright notices and legends are affixed to each reproduced copy.

The right to print or otherwise make available copies of the Documentation is limited to the period during which the applicable license for such software remains in full force and effect. Should the license terminate for any reason, it is your responsibility to certify in writing to Quest Software, Inc and/or its affiliates that all copies and partial copies of the Documentation have been returned to Quest Software, Inc and/or its affiliates or destroyed.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, QUEST SOFTWARE, INC. PROVIDES THIS DOCUMENTATION “AS IS” WITHOUT WARRANTY OF ANY KIND, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT WILL QUEST SOFTWARE, INC. BE LIABLE TO YOU OR ANY THIRD PARTY FOR ANY LOSS OR DAMAGE, DIRECT OR INDIRECT, FROM THE USE OF THIS DOCUMENTATION, INCLUDING WITHOUT LIMITATION, LOST PROFITS, LOST INVESTMENT, BUSINESS INTERRUPTION, GOODWILL, OR LOST DATA, EVEN IF QUEST SOFTWARE, INC. IS EXPRESSLY ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH LOSS OR DAMAGE.

The use of any software product referenced in the Documentation is governed by the applicable license agreement and such license agreement is not modified in any way by the terms of this notice.

The manufacturer of this Documentation is Quest Software, Inc and/or its affiliates.

Provided with "Restricted Rights." Use, duplication or disclosure by the United States Government is subject to the restrictions set forth in FAR Sections 12.212, 52.227-14, and 52.227-19(c)(1) - (2) and DFARS Section 252.227-7014(b)(3), as applicable, or their successors.

Copyright © 2022 Quest Software, Inc and/or its affiliates All rights reserved. All trademarks, trade names, service marks, and logos referenced herein belong to their respective companies.

## Contact erwin

### Understanding your Support

Review [support maintenance programs and offerings](#).

### Registering for Support

Access the [erwin support](#) site and click **Sign in** or **Sign up** to register for product support.

### Accessing Technical Support

For your convenience, erwin provides easy access to "One Stop" support for all editions of [erwin Data Modeler](#), and includes the following:

- Online and telephone contact information for technical assistance and customer services
- Information about user communities and forums
- Product and documentation downloads
- erwin Support policies and guidelines
- Other helpful resources appropriate for your product

For information about other erwin products, visit <http://erwin.com/products>.

### Provide Feedback

If you have comments or questions, or feedback about erwin product documentation, you can send a message to [techpubs@erwin.com](mailto:techpubs@erwin.com).

### erwin Data Modeler News and Events

Visit [www.erwin.com](http://www.erwin.com) to get up-to-date news, announcements, and events. View video demos and read up on customer success stories and articles by industry experts.



## Contents

---

Introduction .....	9
ArangoDB Support .....	11
Reverse Engineering Models .....	13
Reverse Engineering Options for ArangoDB .....	25
Forward Engineering Models .....	30
Forward Engineering Options for ArangoDB .....	39
Comparing Changes using Complete Compare .....	43
Migrating Relational Models to ArangoDB Models .....	57
Migration by Changing the Target Database .....	57
Migration by Deriving a Model .....	59
Amazon Keyspaces Support .....	65
Reverse Engineering Models .....	67
Reverse Engineering Options for Amazon Keyspaces .....	80
Forward Engineering Models .....	85
Forward Engineering Options for Amazon Keyspaces .....	91
Comparing Changes using Complete Compare .....	94
Migrating Relational Models to Amazon Keyspaces Models .....	107
Migration by Changing the Target Database .....	107
Migration by Deriving a Model .....	109
Google BigQuery Support .....	115
Reverse Engineering Models .....	117
Reverse Engineering Options for Google BigQuery .....	126

---

Forward Engineering Models .....	130
Forward Engineering Options for Google BigQuery .....	135
Comparing Changes using Complete Compare .....	140
Neo4j Support .....	153
Reverse Engineering Models .....	155
Reverse Engineering Options for Neo4j .....	167
Forward Engineering Models .....	172
Forward Engineering Options for Neo4j .....	181
Comparing Changes using Complete Compare .....	185
Migrating Relational Models to Neo4j Models .....	199
Migration by Changing the Target Database .....	199
Migration by Deriving a Model .....	201
Parquet Support .....	209
Reverse Engineering Models .....	210
Reverse Engineering Options for Parquet .....	213
Forward Engineering Models .....	216
Forward Engineering Options for Parquet .....	221
Comparing Changes using Complete Compare .....	224
Migrating Relational Models to Parquet Models .....	234
Migration by Changing the Target Database .....	234
Migration by Deriving a Model .....	236
Databricks Support .....	242
Reverse Engineering Models .....	244

---

Reverse Engineering Options for Databricks .....	255
Forward Engineering Models .....	260
Forward Engineering Options for Databricks .....	269
Comparing Changes using Complete Compare .....	273
DynamoDB Support .....	288
Reverse Engineering Models .....	289
Reverse Engineering Options for DynamoDB .....	299
Forward Engineering Models .....	304
Forward Engineering Options for DynamoDB .....	312
Comparing Changes using Complete Compare .....	316
Migrating Relational Models to DynamoDB Models .....	326
Migration by Changing the Target Database .....	326
Migration by Deriving a Model .....	328
Couchbase Support .....	333
Central Scheduler .....	334
Scheduling Remote Jobs .....	335
Running Complete Compare .....	345
Productivity and UI Enhancements .....	347
Run Multiple Jobs .....	347
Predefined Reverse Engineering Configurations .....	347
Cassandra: Deriving Models and Advanced Denormalization .....	351
Git Integration .....	356
Connecting to Git Repositories .....	356

---

Committing Forward Engineering Scripts .....	359
Scenario 1: Committing FE Scripts for the First Time .....	360
Scenario 2: Committing Alter Scripts After Making Changes to a Model .....	367
Oracle: View and Materialized View Enhancement .....	376
Azure Synapse: Table Constraint Enhancement .....	378
Snowflake Enhancements .....	379
Object Tagging .....	379
Reverse Engineering Enhancements .....	379
Key-Pair Authentication .....	380
Authentication using Unencrypted Key .....	381
Authentication using an Encrypted Key .....	382
MongoDB: Schema Validation .....	385
Diagramming: Hide and Unhide Diagram Nodes .....	387
Data Vault Enhancements .....	389
Productivity and UI Enhancements .....	390
Copy Neighborhood .....	390
Object Browser .....	391
Column Editor Shortcut .....	392
Graph Display Level .....	393
Generate Diagram Picture in Multiple Formats .....	394
DM Connect for DI .....	396
erwin Mart Server Enhancements .....	397
PostgreSQL Certification .....	398

# Introduction

The Feature Tour guide walks Data Architects, Data Administrators, Application Administrators, Database Administrators, and Partners through the features introduced in erwin Data Modeler (DM) 12.0 release.

The features and enhancements introduced in this release are:

- [ArangoDB](#)
- [Amazon Keyspaces](#)
- [Google BigQuery](#)
- [DynamoDB](#)
- [Neo4j](#)
- [Parquet](#)
- [Databricks](#)
- [PostgreSQL](#)
- [Couchbase 7.0](#)
- [Central Scheduler](#)
- [Google BigQuery](#)
- [MongoDB: Schema Validation](#)
- [Snowflake Enhancements](#)
- [Git Integration](#)
- [Cassandra: Deriving Models and Advanced Denormalization](#)
- [Oracle: View and Materialized View Enhancement](#)
- [Azure Synapse: Table Constraint Enhancement](#)
- [Diagramming: Hide and Unhide Diagram Nodes](#)

## Introduction

---

- [Data Vault Enhancements](#)
- [Productivity and UI Enhancements](#)
- [DM Connect for DI](#)
- [erwin Mart Server Enhancements](#)

For additional information about a feature, in erwin Data Modeler, click **Help > Help Topics** or press **F1**.

## ArangoDB Support

erwin Data Modeler (DM) now supports [ArangoDB 3.8](#) and above as a target database. This implementation supports the following objects:

- Collection
  - Field
  - Index
- Database
- Graph
  - Graph Edge
- Index
- Relationship
- Task
- User ID
- Views

The following is the list of supported data types:

- Array
- Boolean
- Double
- Integer
- Null
- Object
- String

ArangoDB implementation supports all erwin DM features and functions. The following sections walk you through these features:

## ArangoDB Support

---

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)
- [Migrating relational models to ArangoDB models](#)




# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process.

This topic walks you through the steps to reverse engineer an ArangoDB model. For detailed description of each reverse engineering option, refer to the [Reverse Engineering Options](#) topic.


To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to ArangoDB.



3. Click **Next**.  
The Reverse Engineer Process Wizard appears.

## Reverse Engineering Models



4. Click one of the following options:

- **Database:** Use this option to reverse engineer a model from your database.



If you click **Database**, continue to step 5.

- **Script File:** Use this option to reverse engineer a model from a script. Selecting this option enables the File field. Click **Browse** and select the necessary JSON file.



If you click **Script File**, see step 13 below and ensure that Document Count or Document % is not set to zero (0).

5. Click **Next**.

## Reverse Engineering Models

The Connection section appears.

Reverse Engineering Wizard

**Connection**  
Configure database connection options

Overview  
**Connection**  
Databases  
Collections  
Option Set  
Detailed Options  
Scheduler

Database: ArangoDB 3.x  
Authentication: Database Authentication  
User Name:   
Password:

Parameters	Value
Connection Method	DIRECT
Hostname/IP	
Port	
Database	

Connect Disconnect API Connection String

Recent Connections:

< Back Next > OK Cancel Help

Use this section to connect to the database from which you want to reverse engineer the model. You can connect to the database directly. The following table explains the connection parameters:


Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Select <b>Direct</b> to connect to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server	

## Reverse Engineering Models

	where your database is hosted	
Port	Specifies the port configured for your database	Default port number is 8529.
Database	Specifies the name of the database to which you want to connect	

6. Click **Connect**.


On successful connection, your connection information is displayed under Recent Connections.





7. Click **Next**.

## Reverse Engineering Models


The Database section appears. It displays a list of available databases.



8. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click .




This moves the selected databases under Selected Databases.



9. Click **Next**.


The Collection section appears. It displays a list of available collections in the databases that you selected in step 8.


## Reverse Engineering Models




10. Use the following options:

- **Document Count/Document (%):** Use this option to specify the number of documents or percentage of total records that the newly generated model schema would contain.
- **Sampling:** Use the Sequence sampling method to sample records in the selected collections. Sampling enables you to retrieve right estimates for accurate collection schema generation.

11. Under **Available Collections**, select the collections that you want to reverse engineer. Then, click .



This moves the selected collections under Selected Collections.




12. Click **Next**.

The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.




## Reverse Engineering Models



13. Click **Next**.

The Detail Options section appears. Set up appropriate options based on your requirement.

## Reverse Engineering Models



The image shows the 'Reverse Engineering Wizard' window, specifically the 'Detailed Options' step. The window has a title bar with standard Windows controls. On the left is a vertical sidebar with a list of steps: Overview, Connection, Databases, Collections, Option Set, Detailed Options (which is highlighted with a white background), and Scheduler. The main area of the window is titled 'Detailed Options' with the subtitle 'Configure detailed reverse engineering options.' Below this, there are two sections: 'NSM Options' and 'Reverse Engineer'. The 'NSM Options' section contains a 'Glossary CSV File:' label followed by a text input field and a 'Browse...' button. The 'Reverse Engineer' section is currently empty. At the bottom of the main area, there are two groups of radio buttons. The first group is 'Case Conversion of Physical Names' with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Force. The second group is 'Case Conversion of Logical Names' with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Mixed. At the very bottom of the window are four buttons: '< Back', 'Next >', 'OK', 'Cancel', and 'Help'. The 'Next >' button is highlighted with a blue border.

Reverse Engineering Wizard

**Detailed Options**  
Configure detailed reverse engineering options.

Overview  
Connection  
Databases  
Collections  
Option Set  
**Detailed Options**  
Scheduler

NSM Options  
Glossary CSV File:  [Browse...](#)

Reverse Engineer

Case Conversion of Physical Names  
☒ None ☐ lower ☐ UPPER ☐ Force


Case Conversion of Logical Names  
☒ None ☐ lower ☐ UPPER ☐ Mixed

< Back **Next >** OK Cancel Help


14. Click **OK**.

## Reverse Engineering Models

The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.




ArangoDb has two types of collections:

## Reverse Engineering Models

---

- **Documents:** Documents contain data or schema. They are represented by rectangles in the ER diagram. For example, in the above model, **female** is a document.
- **Edges:** Edges contain relationship between document data points. They are represented by curved rectangles in the ER diagram. For example, in the above model, **imdb\_edge\_movies** is an edge.

The ER diagram displays the relationship between two documents via edges. For example, in the following model Characters is rated to Locations via the GOT\_Character\_Resides edge.



## Reverse Engineering Options for ArangoDB

The following are the reverse engineering options for ArangoDB in erwin DM.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or database	<b>Database:</b> Indicates that the model is reverse engineered from database <b>Script File:</b> Indicates that the model is reverse engineered from a script
File	Specifies the script file location	This option is available when Script File is selected.

### Connection

Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Select <b>Direct</b> to connect to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted	
Port	Specifies the port configured for your database	Default port number is 8529.
Database	Specifies the name of the database to which you want to connect	

### Databases

Parameter	Description	Additional Information
Available Data	Specifies a list of available databases	

## Reverse Engineering Options for ArangoDB

bases		
Selected Databases	Specifies a list of selected databases for reverse engineering	
System Objects	Specifies whether system databases are included under the Available Databases	

## Collections

Parameter	Description	Additional Information
Document Count/Document (%)	Specifies the number of documents or percentage of total records that the newly generated model schema would contain	
Sampling	Specifies that the sampling method is Sequence. Sampling enables you to retrieve right estimates for accurate collection schema generation.	
Available Collections	Specifies a list of available collections	
Selected Collections	Specifies a list of selected collections for reverse engineering	

## Option Sets

Parameter	Description	Additional Information
Option Set	Specifies the option set template for reverse engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save the configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.

## Reverse Engineering Options for ArangoDB

<Option Set Name>	Specifies the objects to be reverse engineered according to the selected option set. You can edit this list.	
-------------------	--	--

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	
Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Conversion of Logical Names	Specifies how the case conversion of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model	When you schedule a job on a remote server, ensure the model path is same for remote and

## Reverse Engineering Options for ArangoDB

	should be saved and its name	local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option.  <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set.  <b>Standard Default Option Set:</b> Indicates that



## Reverse Engineering Options for ArangoDB

		standard metadata is included. CC works fast with this option set compared to the Advanced option set.
--	--	--

# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process.

This topic walks you through the steps to forward engineer an ArangoDB model. For detailed description of each forward engineering option refer to the [Forward Engineering Options](#) topic.

To forward engineer a model:

1. Open your ArangoDB model in erwin Data Modeler (DM).




Ensure that you are in the Physical mode.

2. Click **Actions > Schema**.

The Forward Engineer Schema Generation Wizard appears.

## Forward Engineering Models



### 3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.

## Forward Engineering Models

The screenshot shows the 'Forward Engineer Schema Generation Wizard' window. The title bar reads 'Forward Engineer Schema Generation Wizard'. The main heading is 'Schema Generation Options', followed by the subtitle 'This page allows the user to change the Forward Engineer Schema Generation Options.'.

On the left is a sidebar with four tabs: 'Overview', 'Option Selection' (which is selected), 'Collection Filter', and 'Preview'.


The main content area contains the following options:

- Option Set:** A dropdown menu showing 'Default NoSQL Schema Generation'. To its right are buttons: 'Open...', 'Save', 'Save As...', and 'Delete'.
- Database Template:** A text box containing 'ArangoDB.fet'. To its right are buttons: 'Browse...', 'Edit...', and 'Reset'.
- Script Option:** Two checkboxes: 'Pre-Script' and 'Post-Script'.
- Database Syntax Option:** Three checkboxes: 'Use DB' (checked), 'Create', and 'Drop'.
- Collection Syntax Option:** Four checkboxes: 'Create' (checked), 'Drop', 'Insert' (checked), and 'Blank Value'.
- View Syntax Option:** Two checkboxes: 'Create' (checked) and 'Drop'.
- Index Syntax Option:** Two checkboxes: 'Create' (checked) and 'Drop'.
- Tasks Syntax Option:** Two checkboxes: 'Register' and 'Unregister'.
- User Syntax Option:** Three checkboxes: 'Create', 'Drop', and 'Permission'.

4. Click **Next**.


The Collection Filter section appears. It displays a list of collections available in your model.

## Forward Engineering Models




5. Select the collections that you want to forward engineer.

### 6. Click **Preview** to view the schema script.



Use the following options:

- **Auto Error Check:** Select this option to enable auto error check by the forward engineering wizard.
- **Error Check** (

v12 Feature Tour Guide | 34

## Forward Engineering Models


---

refer to the Forward Engineering Wizard - Preview Editor topic.

- **Save** (📁): Use this option to save the generated script in the JSON or BSON format.

7. Click **Generate**.

The ArangoDB Connection page appears.



The ArangoDB Connection dialog box is shown. It has a title bar with a close button (X). The dialog contains the following fields and controls:

- Database:** A dropdown menu with "ArangoDB 3.x" selected.
- Authentication:** A dropdown menu with "Database Authentication" selected.
- User Name:** A text input field.
- Password:** A text input field.
- Parameters Table:** A table with two columns: "Parameters" and "Value".

Parameters	Value
Connection Method	DIRECT
Hostname/IP:	
Port:	
Database:	
- Recent Connections:** A list box with a scrollbar, currently empty.
- Buttons:** "Connect", "Disconnect", "Close", and "Help".


8. Enter username, password, and appropriate connection parameters to connect the required database. Then, click **Connect**.



## Forward Engineering Models



The objects move to a database entered on the ArangoDB Connection page irrespective of the databases entered on the object editor pages. If you want to move objects to databases as entered on object editors page then do not enter any database on the ArangoDB Connection page.


The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.




The forward engineering process creates database objects in the database entered on the ArangoDB Connection page. For example, in the following image, the forward engineering process creates 13 collections in the ERWINSALES database. ArangoDB represents edge collections using  whereas document collections are represented using .



## Forward Engineering Models



This process creates six graphs in ERWINSALES database.



You can view graph properties by clicking the required graph. For example, the following Edit Graph page displays the properties of the social graph.

## Forward Engineering Models

Edit Graph

Name:

social

i

Shards:

1

i

Replication factor:

3

i

Write concern:

1

i

+

Edge definitions\*:

× relation

i

fromCollections\*:

× female × male

i

toCollections\*:

× female × male

i

Delete

Reset display settings

Cancel

Save

## Forward Engineering Options for ArangoDB

The following are the forward engineering options for ArangoDB in erwin DM.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.
Database Template	Specifies the database template for controlling schema generation	<b>Browse:</b> Use this option to browse and select a database template. <b>Edit:</b> Use this option to edit a template in the Template Editor. <b>Reset:</b> Use this option to reset the Database Template option.
Script Option	Specifies the script option for the schema generation	<b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed
Database Syntax Option	Specifies the database syntax options for the schema generation	<b>Use DB:</b> Indicates whether the Use DB syntax for databases is executed <b>Create:</b> Indicates whether the Create syntax for databases is executed <b>Drop:</b> Indicates whether the Drop syntax for databases is executed

## Forward Engineering Options for ArangoDB

Collection Syntax Option	Specifies the collection syntax options for the schema generation	<b>Create:</b> Indicates whether the Create syntax for collections is executed <b>Drop:</b> Indicates whether the Drop syntax for collections is executed <b>Insert:</b> Indicates whether the Insert syntax for collections is executed <b>Blank Value:</b> Indicates whether the Blank Value syntax for collections is executed
View Syntax Option	Specifies the view syntax options for the schema generation	<b>Create:</b> Indicates whether the Create syntax for views is executed <b>Drop:</b> Indicates whether the Drop syntax for views is executed
Index Syntax Option	Specifies the index syntax options for the schema generation	<b>Create:</b> Indicates whether the Create syntax for indexes is executed <b>Drop:</b> Indicates whether the Drop syntax for indexes is executed
Tasks Syntax Option	Specifies the task syntax options for the schema generation	<b>Register:</b> Indicates whether the Register syntax for tasks is executed <b>Unregister:</b> Indicates whether the Unregister syntax for tasks is executed
User Syntax Option	Specifies user syntax options for the schema generation	<b>Create:</b> Indicates whether the Create syntax for users is executed <b>Drop:</b> Indicates whether the Drop syntax for users is executed <b>Permission:</b> Indicates whether the Permission syntax for users is executed
Graph Syntax Option	Specifies graph syntax options for the schema generation	<b>Create:</b> Indicates whether the Create syntax for graphs is executed <b>Drop:</b> Indicates whether the Drop syntax for graphs is executed

## Collection Filter

Parameter	Description	Additional Information
Collections	Specifies the selected Collections for the schema generation	
Display either Logical Names or Physical Names		<p><b>Logical Names:</b> Indicates that only logical names of the collections are included in the generated schema</p> <p><b>Physical Names:</b> Indicates that only physical names of the collections are included in the generated schema</p> <p><b>Physical Names, show owner:</b> Indicates that physical names and owners of the collections are included in the generated schema</p> <p><b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the collections are included in the generated schema. Owners of the collections are displayed using User.</p>
Select all of the items in the list	Use this option to select all the collections in the list.	
Unselect all of the items in the list	Use this option to unselect all the collections.	
Select all unselected items, and unselect all selected items	Use this option to select all the unselected collections and unselect all the previously selected collections.	

## Preview

## Forward Engineering Options for ArangoDB

Parameter	Description	Additional Information
Viewer	Displays the schema in the viewer editor	<b>Collapse All:</b> Use this option to collapse all the nodes. <b>Search:</b> Use this option to search a text entered in the search box. <b>Find Previous:</b> Use this option to navigate to previous search string in the search results <b>Find Next:</b> Use this option to navigate to next search string in the search result.
Text	Displays the schema in the text editor	<b>Save:</b> Use this option to save the generated schema. <b>Search:</b> Use this option to search through the generated schema. <b>Print:</b> Use this option to print the generated schema. <b>Replace:</b> Use this option to find and replace text in the generated schema. <b>Copy:</b> Use this option to copy the selected text in the schema. <b>Text Options:</b> Use this option to edit window settings, fonts, and syntax color. <b>Error Check:</b> Use this option to check errors in the forward engineering script. <b>Git:</b> Use this option to commit the FE script to a Git repository.


# Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.


This topic walks you through the steps to compare an ArangoDB model with database.

To compare models with database:

1. Open your ArangoDB model in erwin Data Modeler (DM).

 Ensure that you are in the Physical mode.


For example, the following image uses an ArangoDB model with 42 collections.



2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model section appears.

## Comparing Changes using Complete Compare




### 3. Click **Database/Script**.

By default, the Allow Demand Loading option is selected.




## Comparing Changes using Complete Compare



### 4. Click **Load**.


The New Model dialog box appears. This starts the reverse engineering process to pull a model from the database to compare.



## Comparing Changes using Complete Compare


5. Ensure that the Database is set to the correct one. In this case, ArangoDB. Then, click **Next**.


The Reverse Engineer Process Wizard appears.




6. Click **Database**. Then, click **Next**.  
The Connection section appears. Use this section to connect to the database from which you want to [reverse engineer the model](#).
7. After connection is established, click **Next**.  
The Database section appears. It displays a list of available databases.


## Comparing Changes using Complete Compare




8. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click . This moves the selected databases under Selected Databases.

## Comparing Changes using Complete Compare



9. Click **Next** and in the Collection section, click . This selects all the available collections. Also, ensure that the Document Count/Document % is not set to zero (0).


## Comparing Changes using Complete Compare



10. Click **Next** and in the Option Set section, keep the default configuration.
11. Click **Next** and in the Detail Options section, keep the default configuration.
12. Click **OK**.

The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.


## Comparing Changes using Complete Compare



13. Click **Next** and in the Type Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



14. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

For example, the following image shows the default options.




15. Click **Next** and in the Right Object Selection section, select the appropriate options.



## Comparing Changes using Complete Compare

For example, the following image shows the default options.





16. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.

For example, the following image shows that the frenchCity collection is available in your model but not in the database.

## Comparing Changes using Complete Compare



Select the frenchCity collection and click . This will move the frenchCity collection to the right model (from the database). Similarly, resolve other differences.

17. As differences were moved to the right model, click .  
This launches the Forward Engineering Alter Script Generation Wizard.

## Comparing Changes using Complete Compare

18. Click **Option Selection** and clear all the **Drop** check boxes.


The screenshot shows the 'Forward Engineer Alter Script Schema Generation Wizard' window, specifically the 'Option Selection' tab. The window has a sidebar on the left with tabs: 'Overview', 'Option Selection' (selected), 'Collection Filter', and 'Preview'. The main area contains several sections with checkboxes:

- Script Option:** ☐ Pre-Script, ☐ Post-Script
- Database Syntax Option:** ☒ Use DB, ☒ Create, ☐ Drop
- Collection Syntax Option:** ☒ Create, ☐ Drop, ☒ Insert, ☐ Blank Value
- View Syntax Option:** ☒ Create, ☐ Drop
- Index Syntax Option:** ☒ Create, ☐ Drop
- Tasks Syntax Option:** ☒ Register, ☐ Unregister
- User Syntax Option:** ☒ Create, ☐ Drop, ☒ Permission

At the top, there is a dropdown menu for 'Option Set' (currently set to 'Select the options for DB Sync') and buttons for 'Open...', 'Save', 'Save As...', and 'Delete'. Below that is a 'Database Template' field (set to 'ArangoDB.fet') with 'Browse...', 'Edit...', and 'Reset' buttons. At the bottom right, there are navigation buttons: '< Back', 'Next >', 'Generate', 'OK' (highlighted), 'Cancel', and 'Help'.

19. Click **Collection Filter** and select or verify the collections to be included on the forward engineering script.

## Comparing Changes using Complete Compare



20. Click **Preview** to view and verify the alter script.
21. Click **Generate** and connect to your ArangoDB database.  
The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.
22. Click **OK**. Then click **Finish**.  
This closes the Resolve Differences dialog box and displays the Complete Compare wizard.
23. Click **Close**.

# Migrating Relational Models to ArangoDB Models

You can migrate your relational models to ArangoDB models in two ways:


- [Changing the target database](#)
- [Deriving a model](#)

This topic walks you through the steps to migrate a SQL Server model to an ArangoDB model.


## Migration by Changing the Target Database

To migrate by changing the target database, follow these steps:

1. Open your relational model in erwin Data Modeler (DM).

 Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.




2. On the ribbon, click **Actions > Target Database** or on the status bar, click the database name.


The erwin Data Modeler -- Target Server screen appears.

## Migrating Relational Models to ArangoDB Models

---



3. In the **Database** drop-down list, select ArangoDB.




4. Click **OK**.

The conversion process starts.

Once the conversion is complete, the existing model is migrated to an ArangoDB database.

## Migrating Relational Models to ArangoDB Models



In the **Objects Count** pane, note that instead of tables and columns, we now have collections and fields. The migration process converts and merges multiple tables, columns, and relationships to the ArangoDB format.

## Migration by Deriving a Model

To migrate by deriving a model, follow these steps:


1. Open your relational model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.

## Migrating Relational Models to ArangoDB Models



2. On the ribbon, click **Actions > Design Layers > Derive New Model**.

The Derive Model screen appears. By default, the Source Model is set to your current model.



## Migrating Relational Models to ArangoDB Models

Derive Model

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level: Unknown

[Overview](#)  
[Source Model](#)  
**[Target Model](#)**  
[Type Selection](#)  
[Object Selection](#)  
[Naming Standards](#)

New Model Type  
☐ Logical ☐ Physical ☒ Logical/Physical

Create Using Template:  
Blank Logical/Physical Model

Remove Browse File System... Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

Target Database  
Database: SQL Server Version: 2019

< Back Next > Derive Close Help

3. In the **Database** drop-down list, select **ArangoDB**.


4. Click **Next**.



If the Type Resolution screen appears, click **Finish**.

The Type Selection section appears.

## Migrating Relational Models to ArangoDB Models




5. Select the types of objects that you want to derive into the target ArangoDB model.

6. Click **Next**.

The Object Selection section appears. Based on the object types you selected in step 5, it displays a list of objects.


## Migrating Relational Models to ArangoDB Models



7. Select the objects that you want to derive into the target ArangoDB model.


8. Click **Derive**.

The model derivation process starts.



## Migrating Relational Models to ArangoDB Models

Once the conversion is complete, the existing model is migrated to a NoSQL database.



In the **Objects Count** pane, note that instead of tables and columns, we now have collections and fields. The migration process converts and merges multiple tables, columns, and relationships to the ArangoDB format.

# Amazon Keyspaces Support

erwin Data Modeler (DM) now supports [Amazon Keyspaces](#) as a target database. This implementation supports the following objects:

- Keyspaces
- Tables
  - Columns
  - Indexes

Following are the supported data types:

- ASCII
- BIGINT
- BLOB
- BOOLEAN
- COUNTER
- DATE
- DECIMAL
- DOUBLE
- FLOAT
- INET
- INT
- LIST
- MAP
- SET
- SMALLINT
- TEXT
- TIME

## Amazon Keyspaces Support

---

- TIMESTAMP
- TIMEUUID
- TINYINT
- TUPLE
- UUID
- VARCHAR
- VARINT

Amazon Keyspaces implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)
- [Converting relational models to Amazon Keyspaces models](#)


# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process.

This topic walks you through the steps to reverse engineer an Amazon Keyspaces model. For detailed description of reverse engineering options, refer to the [Reverse Engineering Options](#) topic.


To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to Amazon Keyspaces.



3. Click **Next**.  
The Reverse Engineering Wizard appears.

## Reverse Engineering Models



4. Click one of the following options:

- **Keyspaces:** Use this option to reverse engineer a model from your database.



If you click **Keyspaces**, continue to step 5.

- **Script File:** Use this option to reverse engineer a model from a script. Selecting this option enables the File field. Click **Browse** and select the necessary script file.



If you click **Script File**, see step 13 below.

5. Click **Next**.



## Reverse Engineering Models

The Connection section appears.

Reverse Engineering Wizard

**Connection**  
Configure database connection options

Overview  
**Connection**  
Keyspaces  
Tables  
Option Set  
Detailed Options  
Scheduler

Database: AWS Keyspace 2.x  
Authentication: Database Authentication  
User Name:   
Password:

Parameters	Value
Connection Method	DIRECT
Hostname/IP	<input type="text"/>
Port	9142
SSL Certificate Path	C:\SSL\sf-class2-root.crt

Connect Disconnect API Connection String

Recent Connections:

< Back Next > OK Cancel Help

6. Enter your **User Name** and **Password**.

The following table explains the connection parameters.


Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Select <b>Direct</b> to connect to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted in the following format: <i>cassandra.&lt;region&gt;.amazonaws.com</i>	For example, <i>cassandra.us-east-2.amazonaws.com</i>  This option is available when Connection Method is set to Direct.

## Reverse Engineering Models

Port	Specifies the port configured for your data base	For example, 9142  This option is available when Connection Method is set to Direct.
SSL Certificate Path	Specifies the path to the SSL certificate in the following format:  <i>C:\&lt;file name&gt;.crt</i>	For example, C:\SSL\sf-class2-root.crt  This option is available when Connection Method is set to Direct.

7. Click **Connect**.


On successful connection, your connection information is displayed under Recent Connections.





8. Click **Next**.

## Reverse Engineering Models


The Database section appears. It displays a list of available databases.



9. Under **Available Keyspaces**, select the keyspaces that you want to reverse engineer. Then, click .




This moves the selected databases under Selected Keyspaces.



10. Click **Next**.

The Collection section appears. It displays a list of available collections in the databases that you selected in step 8.


## Reverse Engineering Models



11. Click **Next**.

The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.


## Reverse Engineering Models



12. Click **Next**.

The Detail Options section appears. Set up appropriate options based on your requirement.

## Reverse Engineering Models



The image shows a screenshot of the 'Reverse Engineering Wizard' dialog box, specifically the 'Detailed Options' tab. The dialog has a title bar with standard window controls. On the left is a vertical sidebar with a list of steps: Overview, Connection, Keyspaces, Tables, Option Set, Detailed Options (which is highlighted with a white background), and Scheduler. The main area of the dialog is titled 'Detailed Options' with the subtitle 'Configure detailed reverse engineering options.' Below this, there are two sections: 'NSM Options' and 'Reverse Engineer'. The 'NSM Options' section contains a 'Glossary CSV File:' label followed by a text input field and a 'Browse...' button. The 'Reverse Engineer' section is currently empty. At the bottom of the main area, there are two groups of radio buttons. The first group is 'Case Conversion of Physical Names' with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Force. The second group is 'Case Conversion of Logical Names' with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Mixed. At the very bottom of the dialog are five buttons: '< Back', 'Next >', 'OK', 'Cancel', and 'Help'.

Reverse Engineering Wizard

**Detailed Options**  
Configure detailed reverse engineering options.

Overview  
Connection  
Keyspaces  
Tables  
Option Set  
**Detailed Options**  
Scheduler

NSM Options  
Glossary CSV File:  [Browse...](#)

Reverse Engineer

Case Conversion of Physical Names  
☒ None ☐ lower ☐ UPPER ☐ Force

Case Conversion of Logical Names  
☒ None ☐ lower ☐ UPPER ☐ Mixed


< Back Next > OK Cancel Help

13. Click **OK**.

## Reverse Engineering Models


---

The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.






You can edit the shape of the nodes to look like the standard table-like structure. On the ribbon click **View > Field**. You can also change label color, size, and caption using the properties pane.

## Reverse Engineering Models


Along with Keyspaces and Tables, other objects such as Columns and Indexes are also ret-



You can view these objects via the model diagram or view their properties via the Model Explorer. Right-click an object and then, click the required Properties option. For example, on the model diagram, right click a table and then, click Table Properties. The Amazon Keyspaces table editor appears. You can view the table's CREATE statement on the No SQL tab, as seen , the table, Media has four properties, audio, video, id, and name to

### Reverse Engineering Models

store additional information.



## Reverse Engineering Options for Amazon Keyspaces

The following are the reverse engineering options for Amazon Keyspaces in erwin DM.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or keyspaces	<b>Keyspaces:</b> Indicates that the model is reverse engineered from keyspaces  <b>Script File:</b> Indicates that the model is reverse engineered from a script
File	Specifies the script file location	This option is available when Script File is selected.

### Connection

Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Select <b>Direct</b> to connect to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted in the following format:  <i>cassandra.&lt;region&gt;.amazonaws.com</i>	For example, <i>cassandra.us-east-2.amazonaws.com</i>  This option is available when Connection Method is set to Direct.
Port	Specifies the port configured for your database	For example, <i>9142</i>  This option is available when Connection Method is set to Direct.
SSL Certificate Path	Specifies the path to the SSL certificate in the following format:	For example, <i>C:\SSL\sfc-class2-root.crt</i>

## Reverse Engineering Options for Amazon Keyspaces

	<i>C:\&lt;file name&gt;.crt</i>	This option is available when Connection Method is set to Direct.
--	---------------------------------	---

## Keyspaces

Parameter	Description	Additional Information
System Objects	Specifies whether system objects are available under Available Keyspaces	
Available Key-spaces	Specifies a list of available keyspaces	
Selected Key-spaces	Specifies a list of selected keyspaces for reverse engineering	

## Tables

Parameter	Description	Additional Information
Available Tables	Specifies a list of available tables	
Selected Tables	Specifies a list of selected tables for reverse engineering	

## Option Sets

Parameter	Description	Additional Information
Option Set	Specifies the option set template for reverse engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save the configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location.

## Reverse Engineering Options for Amazon Keyspaces

		<b>Delete:</b> Use this option to delete an option set.
<Option Set Name>	Specifies the objects to be reverse engineered according to the selected option set. You can edit this list.	

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	
Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Conversion of Logical Names	Specifies how the case conversion of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

## Reverse Engineering Options for Amazon Keyspaces

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model should be saved and its name	When you schedule a job on a remote server, ensure the model path is same for remote and local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option. <b>Speed Option Set:</b> Indicates that only the essen-

Reverse Engineering Options for Amazon Keyspaces

		<p>tial metadata is included. CC works the fastest with this option set.</p> <p><b>Standard Default Option Set:</b> Indicates that standard metadata is included. CC works fast with this option set compared to the Advanced option set.</p>
--	--	---




# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process.

This topic walks you through the steps to forward engineer an Amazon Keyspaces model. For detailed description of forward engineering options, refer to the [Forward Engineering Options](#) topic.


To forward engineer an Amazon Keyspaces model:

1. Open your Amazon Keyspaces model in erwin Data Modeler (DM).



2. Click **Actions > Schema**.


The Forward Engineer Schema Generation Wizard appears.



3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.


## Forward Engineering Models



4. Click **Next**.


The Table Filter section appears. It displays a list of tables available in your model.

## Forward Engineering Models



5. Select the tables that you want to forward engineer.


### 6. Click **Preview** to view the schema script.



Use the following options:


- **Copy** (📄): Use this option to copy the script.
- **Save** (💾): Use this option to save the generated script in the CQL or SQL format.
- **Search** (🔍): Use this option to search through the generated schema.
- **Print** (🖨): Use this option to print the generated schema.
- **Replace** (🔄): Use this option to find and replace in the generated schema.

## Forward Engineering Models

- **Text Options** (


7. Click **Generate**.

The Amazon Keyspaces Connection editor appears.



The Amazon Keyspaces Connection dialog box is shown. It contains the following fields and controls:

- Database:** A dropdown menu set to "Amazon Keyspaces".
- Authentication:** A dropdown menu set to "Database Authentication".
- User Name:** A text input field containing "user\_1234".
- Password:** A text input field.
- Parameters Table:** A table with two columns: "Parameters" and "Value".


Parameters	Value
Connection Method	DIRECT
Hostname/IP:	localhost:9142
Port:	9142
SSL Certificate Path	C:\SSL\sfl-class2-root.crt 
- Recent Connections:** A list box with a scrollbar, currently empty.
- Buttons:** "Connect", "Disconnect", "Close", and "Help".

8. Enter username, password, and appropriate connection parameters to connect the required database. Then, click **Connect**.



Objects in your model move to the database mentioned on the Amazon Keyspaces Connection screen irrespective of the databases defined on the object editor screens. If you want to retain objects in their respective databases as defined on the object editor screens, keep the database parameter blank.

The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.



## Forward Engineering Options for Amazon Keyspaces

Following are the forward engineering options for Amazon Keyspaces.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at an external location. <b>Delete:</b> Use this option to delete an option set.
Database Template	Specifies the database template for controlling schema generation	<b>Browse:</b> Use this option to browse and select a database template. <b>Edit:</b> Use this option to edit a template in the Template Editor. <b>Reset:</b> Use this option to reset the Database Template option.
Script Option	Specifies the script option for schema generation	<b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed
Keyspace Syntax Option	Specifies the keyspace syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for keyspaces is executed <b>Drop:</b> Indicates whether the Drop syntax for keyspaces is executed
Table Syntax Option	Specifies the table syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for tables is executed

## Forward Engineering Options for Amazon Keyspaces

		<b>Drop:</b> Indicates whether the Drop syntax for tables is executed
--	--	---

### Table Filter

Parameter	Description	Additional Information
Tables	Specifies the selected tables for schema generation	
Display either Logical Names or Physical Names	Specifies the database template for controlling schema generation	<b>Logical Names:</b> Indicates that only logical names of the records are included in the generated schema  <b>Physical Names:</b> Indicates that only physical names of the records are included in the generated schema  <b>Physical Names, show owner:</b> Indicates that physical names and owners of the records are included in the generated schema  <b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the records are included in the generated schema. Owners of the records are displayed using User.
Select all of the items in the list	Use this option to select all the records in the list.	
Unselect all of the items in the list	Use this option to clear all the records.	
Select all unselected items, and unselect all selected items	Use this option to select all the unselected records and clear all the previously selected records.	



### Preview

Parameter	Description	Additional Information
Text	Displays the schema in the text editor	<p><b>Save:</b> Use this option to save the generated schema.</p> <p><b>Search:</b> Use this option to search through the generated schema.</p> <p><b>Print:</b> Use this option to print the generated schema.</p> <p><b>Replace:</b> Use this option to find and replace text in the generated schema.</p> <p><b>Copy:</b> Use this option to copy the selected text in the schema.</p> <p><b>Text Options:</b> Use this option to edit window settings, fonts, syntax color.</p>

## Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.

This topic walks you through the steps to compare an Amazon Keyspaces model with database.


To compare models with database:

1. Open your Amazon Keyspaces model.



Ensure that you are in the Physical mode.

For example, the following image uses an Amazon Keyspaces model with 28 records.




2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model.

## Comparing Changes using Complete Compare

---


Hence, the Right Model section appears.



3. Click **Database/Script**.


By default, the Allow Demand Loading option is selected.

## Comparing Changes using Complete Compare



### 4. Click **Load**.


The New Model dialog box appears. This starts the reverse engineering process to pull a model from the database to compare.



## Comparing Changes using Complete Compare


5. Ensure that the Database is set to the correct one. In this case, Amazon Keyspaces. Then, click **Next**.


The Reverse Engineering Wizard appears.




6. Click **Keyspaces**. Then, click **Next**.  
The Connection section appears. Use this section to connect to the database from which you want to [reverse engineer the model](#).
7. After connection is established, click **Next**.  
The Keyspaces section appears. It displays a list of available keyspaces.

## Comparing Changes using Complete Compare





8. Under **Available Keyspaces**, select the keyspaces that you want to reverse engineer. Then, click .

This moves the selected keyspaces under Selected Keyspaces.




## Comparing Changes using Complete Compare

- Click **Next** and in the Tables section, click . This selects all the available tables.



- Click **Next** and in the Option Set section, keep the default configuration.
- Click **Next** and in the Detail Options section, keep the default configuration.
- Click **OK**.  
The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.

## Comparing Changes using Complete Compare




13. Click **Next** and in the Type Selection section, select the appropriate options.



## Comparing Changes using Complete Compare

---


For example, the following image shows the default options.



14. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



15. Click **Next** and in the Right Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

For example, the following image shows the default options.





16. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.

For example, the following image shows that the point\_id table is available in your model but not in the database.

## Comparing Changes using Complete Compare




Select the Rating collection and click . This will move the point\_id table to the right model (from the database). Similarly, resolve other differences.


17. As differences were moved to the right model, click . This launches the Forward Engineering Alter Script Generation Wizard.

## Comparing Changes using Complete Compare

18. Click **Option Selection** and clear all the **Drop** check boxes.



19. Click **Table Filter** and select or verify the tables to be included in the forward engineering script.



20. Click **Preview** to view and verify the alter script.

## Comparing Changes using Complete Compare

---

21. Click **Generate** and connect to your Amazon Keyspaces database.  
The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.
22. Click **OK**. Then click **Finish**.  
This closes the Resolve Differences dialog box and displays the Complete Compare wizard.
23. Click **Close**.

# Migrating Relational Models to Amazon Keyspaces Models

You can migrate your relational models to Amazon Keyspaces models in two ways:


- [Changing the target database](#)
- [Deriving a model](#)

This topic walks you through the steps to migrate a SQL Server model to an Amazon Key-spaces model.


## Migration by Changing the Target Database

To migrate by changing the target database, follow these steps:

1. Open your relational model in erwin Data Modeler (DM).

 Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.




2. On the ribbon, click **Actions > Target Database** or on the status bar, click the database name.


The erwin Data Modeler -- Target Server screen appears.

## Migrating Relational Models to Amazon Keyspaces Models

---



3. In the **Database** drop-down list, select Amazon Keyspaces.




4. Click **OK**.

The conversion process starts.

Once the conversion is complete, the existing model is migrated to an Amazon Keyspaces database.



## Migrating Relational Models to Amazon Keyspaces Models



In the **Objects Count** pane, note that instead of databases, we now have keyspaces. The migration process converts and merges multiple tables, columns, and relationships to the Amazon Keyspaces format.

## Migration by Deriving a Model

To migrate by deriving a model, follow these steps:


1. Open your relational model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.

## Migrating Relational Models to Amazon Keyspaces Models



2. On the ribbon, click **Actions > Design Layers > Derive New Model**.

The Derive Model screen appears. By default, the Source Model is set to your current model.

## Migrating Relational Models to Amazon Keyspaces Models

Derive Model

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level: Unknown

[Overview](#)  
[Source Model](#)  
**[Target Model](#)**  
[Type Selection](#)  
[Object Selection](#)  
[Naming Standards](#)

New Model Type  
☐ Logical ☐ Physical ☒ Logical/Physical

Create Using Template:  
Blank Logical/Physical Model

Remove Browse File System... Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

Target Database  
Database: SQL Server Version: 2019

< Back Next > Derive Close Help

3. In the **Database** drop-down list, select **Amazon Keyspaces**.


4. Click **Next**.



If the Type Resolution screen appears, click **Finish**.


The Type Selection section appears.

## Migrating Relational Models to Amazon Keyspaces Models



5. Select the types of objects that you want to derive into the target Amazon Keyspaces model.
6. Click **Next**.  
The Object Selection section appears. Based on the object types you selected in step 5, it displays a list of objects.


## Migrating Relational Models to Amazon Keyspaces Models



7. Select the objects that you want to derive into the target Amazon Keyspaces model.


8. Click **Derive**.

The model derivation process starts.



## Migrating Relational Models to Amazon Keyspaces Models

Once the conversion is complete, the existing model is migrated to an Amazon Keyspaces database.



In the **Objects Count** pane, note that instead of tables and columns, we now have entities and attributes. The migration process converts and merges multiple tables, columns, and relationships to the Amazon Keyspaces format.

## Google BigQuery Support

erwin Data Modeler (DM) now supports [Google BigQuery](#) as a target database. This implementation supports the following objects:

- Dataset
- Function
- Materialized View
- Stored Procedure
- Table
  - Columns
  - Row Access Policy
- View

Following are the supported data types:

- BIGNUMERIC
- BOOLEAN
- BYTES
- DATE
- DATETIME
- FLOAT
- GEOGRAPHY
- INTEGER
- INTERVAL
- NUMERIC
- RECORD/STRUCT
- STRING

## Google BigQuery Support

---

- TIME
- TIMESTAMP

Google BigQuery implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)




# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process.

This topic walks you through the steps to reverse engineer a Google BigQuery model. For detailed description of reverse engineering options, refer to the [Reverse Engineering Options](#) topic.

To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to Google BigQuery.




The screenshot shows the 'New Model' dialog box with the following settings:

- Type:** Logical/Physical (selected)
- Target Server:** Match template target server (unchecked), Database: Google BigQuery, Version: (empty)
- Template:** <Default> (selected), Preserve the template binding (unchecked)

Buttons: Next, Cancel

3. Click **Next**.  
The Reverse Engineering Wizard appears.

## Reverse Engineering Models



4. Click one of the following options:

- **Datasets:** Use this option to reverse engineer a model from your dataset.



If you click **Datasets**, continue to step 5.

- **Script File:** Use this option to reverse engineer a model from a script. Selecting this option enables the File field. Click **Browse** and select the necessary script file.



If you click **Script File**, see step 13 below.

5. Click **Next**.

## Reverse Engineering Models

The Connection section appears.

Reverse Engineering Wizard

**Connection**  
Configure database connection options

Overview  
**Connection**  
Datasets  
Tables  
Option Set  
Detailed Options  
Scheduler

Database: Google BigQuery  
Authentication: Database Authentication  
User Name:   
Password:

Parameters	Value
Connection Method	CONNECTION STRING
Connection String:	

Connect Disconnect API Connection String

Recent Connections:

< Back Next > OK Cancel Help

6. Enter your **User Name** and **Password**.

The following table explains the connection parameters.


Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. <b>Connection String</b> connects to your cluster using a connection string.	
Connection String	Specifies the path to the secure connect JSON file in the following format: <i>C:\&lt;file name&gt;.json</i>	This option is available when Connection Method is set to Connection String

7. Click **Connect**.

On successful connection, your connection information is displayed under Recent


## Reverse Engineering Models


Connections.



8. Click **Next**.


The Datasets section appears. It displays a list of available datasets.




9. Under **Available Datasets**, select the datasets that you want to reverse engineer. Then, click .

## Reverse Engineering Models

---




This moves the selected datasets under Selected Datasets.



### 10. Click **Next**.

The Tables section appears. It displays a list of available tables in the datasets that you selected in step 8.


## Reverse Engineering Models



11. Click **Next**.

The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.


## Reverse Engineering Models



12. Click **Next**.

The Detail Options section appears. Set up appropriate options based on your requirement.

## Reverse Engineering Models



The image shows a screenshot of the 'Reverse Engineering Wizard' dialog box, specifically the 'Detailed Options' step. The window title is 'Reverse Engineering Wizard'. The main heading is 'Detailed Options' with the subtitle 'Configure detailed reverse engineering options.' On the left is a vertical sidebar with navigation links: 'Overview', 'Connection', 'Datasets', 'Tables', 'Option Set', 'Detailed Options' (which is highlighted), and 'Scheduler'. The main area is divided into two sections. The top section, 'NSM Options', contains a 'Glossary CSV File:' label followed by a text input field and a 'Browse...' button. The bottom section, 'Reverse Engineer', contains two groups of radio buttons. The first group, 'Case Conversion of Physical Names', has four options: 'None' (selected), 'lower', 'UPPER', and 'Force'. The second group, 'Case Conversion of Logical Names', has four options: 'None' (selected), 'lower', 'UPPER', and 'Mixed'. At the bottom of the dialog are five buttons: '< Back', 'Next >', 'OK', 'Cancel', and 'Help'.

Reverse Engineering Wizard

**Detailed Options**  
Configure detailed reverse engineering options.

Overview  
Connection  
Datasets  
Tables  
Option Set  
**Detailed Options**  
Scheduler

NSM Options

Glossary CSV File:  [Browse...](#)

Reverse Engineer

Case Conversion of Physical Names  
☒ None ☐ lower ☐ UPPER ☐ Force

Case Conversion of Logical Names  
☒ None ☐ lower ☐ UPPER ☐ Mixed


< Back Next > OK Cancel Help

13. Click **OK**.




## Reverse Engineering Models

The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.



## Reverse Engineering Options for Google BigQuery

Following are the reverse engineering options for Google BigQuery.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or dataset	<b>Datasets:</b> Indicates that the model is reverse engineered from datasets <b>Script File:</b> Indicates that the model is reverse engineered from a script
File	Specifies the script file location	This option is available when Script File is selected.

### Connection

Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. <b>Connection String</b> connects to your cluster using a connection string.	
Connection String	Specifies the path to the secure connect JSON file in the following format:  <i>C:\&lt;file name&gt;.json</i>	This option is available when Connection Method is set to Connection String

### Datasets

Parameter	Description	Additional Information
System Objects	Specifies whether system objects are included under the Available Datasets	
Available Datasets	Specifies a list of available datasets	

## Reverse Engineering Options for Google BigQuery

Selected Data-sets	Specifies a list of selected datasets for reverse engineering	
--------------------	---	--

## Tables

Parameter	Description	Additional Information
Available Tables	Specifies a list of available tables	
Selected Tables	Specifies a list of selected tables for reverse engineering	

## Option Sets

Parameter	Description	Additional Information
Option Set	Specifies the option set template for reverse engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save the configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.
<Option Set Name>	Specifies the objects to be reverse engineered according to the selected option set. You can edit this list.	

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming	

## Reverse Engineering Options for Google BigQuery

	standard glossary file in the .CSV format	
Case Con- version of Physical Names	Specifies how the case con- version of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Con- version of Logical Names	Specifies how the case con- version of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model should be saved and its name	When you schedule a job on a remote server, ensure the model path is same for remote and local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete	Specifies whether the Com-	

## Reverse Engineering Options for Google BigQuery

Compare	Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<p><b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option.</p> <p><b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set.</p> <p><b>Standard Default Option Set:</b> Indicates that standard metadata is included. CC works fast with this option set compared to the Advanced option set.</p>

# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process.

This topic walks you through the steps to forward engineer a Google BigQuery model. For detailed description of forward engineering options, refer to the [Forward Engineering Options](#) topic.

To forward engineer a Google BigQuery model:


1. Open your Google BigQuery model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.

2. Click **Actions > Schema**.

The Forward Engineer Schema Generation Wizard appears.



## Forward Engineering Models

### 3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.

The screenshot shows the 'Forward Engineer Schema Generation Wizard' window, specifically the 'Schema Generation Options' tab. The left sidebar has 'Option Selection' selected. The main area shows the 'Option Set' as 'Default NoSQL Schema Generation' and the 'Database Template' as 'GoogleBigQuery.fet'. Below these are several sections of options, each with 'Create' and 'Drop' checkboxes. The 'Table Syntax Option' section has 'Create' checked. The 'View Syntax Option' and 'Materialized View Syntax Option' sections also have 'Create' checked. The 'Script Option' section has both 'Pre - Script' and 'Post - Script' unchecked. The 'General Syntax Options' section has 'Qualify Names', 'Quote Names', 'If Exists', and 'Comments' all unchecked. The 'Dataset Syntax Option' section has 'Create' unchecked, 'Drop' unchecked, and 'Cascade' unchecked. The 'Function Option' section has 'Create' unchecked and 'Drop' unchecked. The 'Procedure Syntax Option' section has 'Create' unchecked and 'Drop' unchecked. The 'RowAccessPolicy Syntax Option' section has 'Create' unchecked and 'Drop' unchecked. At the bottom are buttons for '< Back', 'Next >', 'Generate', 'OK', 'Cancel', and 'Help'.




Ensure that you keep a backup of your original table before making any changes.

### 4. Click **Next**.

The Table Filter section appears. It displays a list of tables available in your model.


## Forward Engineering Models



5. Select the tables that you want to forward engineer.




### 6. Click **Preview** to view the schema script.



Use the following options:


- **Copy** (📄): Use this option to copy the script.
- **Save** (💾): Use this option to save the generated script in the ERS, SQL, or DDL format.
- **Search** (🔍): Use this option to search through the generated schema.
- **Print** (🖨️): Use this option to print the generated schema.
- **Replace** (🔄): Use this option to find and replace in the generated schema.

## Forward Engineering Models

- **Text Options** (

7. Click **Generate**.

The Google BigQuery Connection screen appears.



Parameters	Value
Connection Method	CONNECTION STRING
Connection String:	<input type="text"/> <span>Down</span>

8. Enter username, password, and appropriate connection parameters to connect the required database. Then, click **Connect**.




Objects in your model move to the database mentioned on the Google BigQuery Connection screen irrespective of the databases defined on



the object editor screens. If you want to retain objects in their respective databases as defined on the object editor screens, keep the database parameter blank.

The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.



## Forward Engineering Options for Google BigQuery

Following are the forward engineering options for Google BigQuery.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set.

## Forward Engineering Models

		<p><b>Save As:</b> Use this option to save an option set either in the model or in the XML format at an external location.</p> <p><b>Delete:</b> Use this option to delete an option set.</p>
Database Template	Specifies the database template for controlling schema generation	<p><b>Browse:</b> Use this option to browse and select a database template.</p> <p><b>Edit:</b> Use this option to edit a template in the Template Editor.</p> <p><b>Reset:</b> Use this option to reset the Database Template option.</p>
Script Option	Specifies the script option for schema generation	<p><b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed</p> <p><b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed</p>
General Syntax Options	Specifies the general syntax options for schema generation	<p><b>Qualify Names:</b> Indicates whether the Qualify names syntax for general properties is executed</p> <p><b>Quote Names:</b> Indicates whether the Quote names syntax for general properties is executed</p> <p><b>If Exists:</b> Indicates whether the If exists syntax for general properties is executed</p> <p><b>Comments:</b> Indicates whether comments are included in the schema</p>
Dataset Syntax Option	Specifies the dataset syntax options for schema generation	<p><b>Create:</b> Indicates whether the Create syntax for datasets is executed</p> <p><b>Drop:</b> Indicates whether the Drop syntax for datasets is executed</p> <p><b>Cascade:</b> Indicates whether the Cascade syn-</p>

## Forward Engineering Models

		tax for datasets is executed
Table Syntax Option	Specifies the table syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for tables is executed <b>Drop:</b> Indicates whether the Drop syntax for tables is executed
Function Option	Specifies the function syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for functions is executed <b>Drop:</b> Indicates whether the Drop syntax for functions is executed
View Syntax Option	Specifies the view syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for views is executed <b>Drop:</b> Indicates whether the Drop syntax for views is executed
Materialized View Syntax Option	Specifies the materialized view syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for materialized views is executed <b>Drop:</b> Indicates whether the Drop syntax for materialized views is executed
Procedure Syntax Option	Specifies the procedure syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for procedures is executed <b>Drop:</b> Indicates whether the Drop syntax for procedures is executed
RowAccessPolicy Syntax Option	Specifies the row access policy syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for row access policies is executed <b>Drop:</b> Indicates whether the Drop syntax for row access policies is executed

## Table Filter

Parameter	Description	Additional Information
Tables	Specifies the selected tables for schema generation	

## Forward Engineering Models

Display either Logical Names or Physical Names		<p><b>Logical Names:</b> Indicates that only logical names of the records are included in the generated schema</p> <p><b>Physical Names:</b> Indicates that only physical names of the records are included in the generated schema</p> <p><b>Physical Names, show owner:</b> Indicates that physical names and owners of the records are included in the generated schema</p> <p><b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the records are included in the generated schema. Owners of the records are displayed using User.</p>
Select all of the items in the list	Use this option to select all the records in the list.	
Unselect all of the items in the list	Use this option to clear all the records.	
Select all unselected items, and unselect all selected items	Use this option to select all the unselected records and clear all the previously selected records.	



Ensure that you keep a backup of your original table before making any changes.

## Preview

Parameter	Description	Additional Information
Text	Displays the schema in the text editor	<p><b>Save:</b> Use this option to save the generated schema.</p> <p><b>Search:</b> Use this option to search through the gen-</p>

		<p>erated schema.</p> <p><b>Print:</b> Use this option to print the generated schema.</p> <p><b>Replace:</b> Use this option to find and replace text in the generated schema.</p> <p><b>Copy:</b> Use this option to copy the selected text in the schema.</p> <p><b>Text Options:</b> Use this option to edit window settings, fonts, syntax color.</p> <p><b>Git:</b> Use this option to commit the FE script to a Git repository.</p>
--	--	---


## Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.


This topic walks you through the steps to compare a Google BigQuery model with database.

To compare models with database:

1. Open your Google BigQuery model.



For example, the following image uses a Google BigQuery model with 4 tables.




2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model section appears.




## Comparing Changes using Complete Compare



3. Click **Database/Script**.


By default, the Allow Demand Loading option is selected.

## Comparing Changes using Complete Compare



### 4. Click **Load**.


The New Model dialog box appears. This starts the reverse engineering process to pull a model from the database to compare.



## Comparing Changes using Complete Compare


5. Ensure that the Database is set to the correct one. In this case, Google BigQuery. Then, click **Next**.


The Reverse Engineering Wizard appears.



6. Click **Datasets**. Then, click **Next**.  
The Connection section appears. Use this section to connect to the database from which you want to [reverse engineer the model](#).
7. After connection is established, click **Next**.  
The Datasets section appears. It displays a list of available datasets.


## Comparing Changes using Complete Compare





8. Under **Available Datasets**, select the datasets that you want to reverse engineer. Then, click . This moves the selected datasets under Selected Datasets .

## Comparing Changes using Complete Compare

---




9. Click **Next** and in the Tables section, click . This selects all the available tables.



10. Click **Next** and in the Option Set section, keep the default configuration.
11. Click **Next** and in the Detail Options section, keep the default configuration.
12. Click **OK**.
- The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.


## Comparing Changes using Complete Compare



13. Click **Next** and in the Type Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



14. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

For example, the following image shows the default options.




15. Click **Next** and in the Right Object Selection section, select the appropriate options.



## Comparing Changes using Complete Compare

For example, the following image shows the default options.





16. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.

For example, the following image shows that the mydataset8.multiplyInputs3 function is available in your model but not in the database.

## Comparing Changes using Complete Compare



Select the Function and click . This will move the mydataset8.multiplyInputs3 table to the right model (from the database). Similarly, resolve other differences.

- As differences were moved to the right model, click .  
This opens the Forward Engineering Alter Script Generation Wizard.


## Comparing Changes using Complete Compare

18. Click **Option Selection** and clear all the **Drop** check boxes.

The screenshot shows the 'Forward Engineer Alter Script Schema Generation Wizard' window. The 'Option Selection' tab is active in the left sidebar. The main area displays various schema generation options. The 'Option Set' is 'Select the options for DB Sync'. The 'Database Template' is 'GoogleBigQuery.fet'. The 'Script Option' section has 'Pre - Script' and 'Post - Script' checkboxes, both of which are unchecked. The 'Dataset Syntax Option' section has 'Create' (checked), 'Drop' (unchecked), and 'Cascade' (unchecked) checkboxes. The 'Table Syntax Option' section has 'Create' (checked) and 'Drop' (unchecked) checkboxes. The 'Function Option' section has 'Create' (checked) and 'Drop' (unchecked) checkboxes. The 'View Syntax Option' section has 'Create' (checked) and 'Drop' (checked) checkboxes. The 'Materialized View Syntax Option' section has 'Create' (checked) and 'Drop' (unchecked) checkboxes. The 'Procedure Syntax Option' section has 'Create' (checked) and 'Drop' (unchecked) checkboxes. The 'RowAccessPolicy Syntax Option' section is empty. At the bottom, there are buttons for '< Back', 'Next >', 'Generate', 'OK', 'Cancel', and 'Help'.

19. Click **Table Filter** and select or verify the tables to be included in the forward engineering script.

## Comparing Changes using Complete Compare



20. Click **Preview** to view and verify the alter script.
21. Click **Generate** and connect to your Google BigQuery database.  
The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.
22. Click **OK**. Then click **Finish**.  
This closes the Resolve Differences dialog box and displays the Complete Compare wizard.
23. Click **Close**.

## Neo4j Support

erwin Data Modeler (DM) now supports [Neo4j 4.2.x and 4.3.x](#) as a target database. This implementation supports the following objects:

- Database
- Global Constraint
- Global Index
- Label
- Node
  - Field
  - Index
- Relationship
- Role
- User ID

Neo4j follows the Database > Label > Node hierarchy. A database can contain multiple labels, each with one or more nodes. A node represents data or information and a label groups the information in nodes together. Each node can have multiple properties (key-value pairs) that represent data.

Nodes can have one or more relationships between them. These relationships describe the connection between source and target nodes. Relationships are always specified with a direction using the "->" notation.

erwin DM focuses on the schema rather than data. Hence, the reverse engineering process retrieves the schema and forward engineering generates the schema; instead of data.

Following are the supported data types:

- ARRAY
- BOOLEAN
- DATE

## Neo4j Support

---

- DURATION
- FLOAT
- INTEGER
- POINT
- STRING
- DATETIME
- LOCALDATETIME
- LOCALTIME
- TIME

Neo4j implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)
- [Converting relational models to Neo4j models](#)


# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process. This topic walks you through the steps to reverse engineer a Neo4j model. While reverse engineering erwin Data Modeler focuses on schema generation rather than data or information.

For detailed description of reverse engineering options, refer to the [Reverse Engineering Options](#) topic.


To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to Neo4j.



3. Click **Next**.  
The Reverse Engineering Wizard appears.

## Reverse Engineering Models



4. Click one of the following options:

- **Database:** Use this option to reverse engineer a model from your database.



If you click **Database**, continue to step 5.

- **Script File:** Use this option to reverse engineer a model from a script. Selecting this option enables the File field. Click **Browse** and select the necessary script file.



If you click **Script File**, see step 13 below.

5. Click **Next**.

The Connection section appears.



## Reverse Engineering Models

Reverse Engineering Wizard

Configure database connection options

Overview

**Connection**

Databases

Label

Option Set

Detailed Options

Scheduler

Database: Neo4j 4.2.x

Authentication: Database Authentication

User Name: neo4j

Password:

Parameters	Value
Connection Method	DIRECT
Hostname/IP	bolt://localhost
Port	7687

Connect Disconnect API Connection String

Recent Connections:

- neo4j://bolt://localhost:7687 (Neo4j) using neo4j
- neo4j://bolt://localhost:7687 (Neo4j 4.2.x) using neo4j

< Back Next > OK Cancel Help

### 6. Enter your **User Name** and **Password**.

The following table explains the connection parameters:

Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Using <b>Direct</b> connects to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted in one of the following formats: <ul style="list-style-type: none"><li><code>Neo4j://&lt;IP address&gt;</code></li><li><code>Neo4j+s://&lt;IP address&gt;</code></li></ul>	For example: <ul style="list-style-type: none"><li><code>Neo4j://localhost</code></li><li><code>Neo4j+s://localhost</code></li><li><code>bolt://localhost</code></li></ul>

## Reverse Engineering Models

	<ul style="list-style-type: none"><li>• <code>bolt://&lt;IP address&gt;</code></li></ul>	
Port	Specifies the port for your database based on your Hostname/IP mechanism	Default port number is 7687.



Other than the above Hostname/IP formats, Neo4j supports the Bolt+s://<IP address> format. However, erwin Data Modeler does not support it at the moment.

### 7. Then, Click **Connect**.

On successful connection, your connection information is displayed under Recent Connections.


The screenshot shows the 'Reverse Engineering Wizard' window with the 'Connection' tab selected. The 'Database' dropdown is set to 'Neo4j 4.2.x' and 'Authentication' is set to 'Database Authentication'. The 'User Name' field contains 'neo4j' and the 'Password' field is masked with dots. Below these fields is a table with two columns: 'Parameters' and 'Value'. The table contains three rows: 'Connection Method' with value 'DIRECT', 'Hostname/IP' with value 'bolt://localhost', and 'Port' with value '7687'. At the bottom of the dialog, there are buttons for 'Connect', 'Disconnect', and 'API Connection String'. Below these buttons is a 'Recent Connections' list showing two entries: 'neo4j://bolt://localhost:7687 (Neo4j 4.2.x) using neo4j' and 'neo4j://bolt://localhost:7687 (Neo4j) using neo4j'. At the very bottom are navigation buttons: '< Back', 'Next >', 'OK', 'Cancel', and 'Help'.


Parameters	Value
Connection Method	DIRECT
Hostname/IP	bolt://localhost
Port	7687


### 8. Click **Next**.

## Reverse Engineering Models

The Databases section appears. It displays a list of available databases.





9. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click .




10. Click **Next**.  
The Label section appears. It displays a list of available labels in the databases that you selected in step 9.

## Reverse Engineering Models




11. Under **Available Labels**, select the labels that you want to reverse engineer. Then, click .



12. Click **Next**.  
The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.


## Reverse Engineering Models



13. Click **Next**.

The Detailed Options section appears. Set up appropriate options based on your requirement.

## Reverse Engineering Models



The image shows a Windows-style dialog box titled "Reverse Engineering Wizard". The main title bar includes standard minimize, maximize, and close buttons. Below the title bar, the text "Reverse Engineering Wizard" is followed by a subtitle "Detailed Options" and a description "Configure detailed reverse engineering options.".

On the left side, there is a vertical navigation pane with the following items: "Overview", "Connection", "Databases", "Label", "Option Set", "Detailed Options" (which is highlighted with a white background), and "Scheduler".


The main content area is divided into two sections. The top section is titled "NSM Options" and contains a label "Glossary CSV File:" followed by a text input field and a "Browse..." button. The bottom section is titled "Reverse Engineer" and contains two groups of radio buttons. The first group is "Case Conversion of Physical Names" with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Force. The second group is "Case Conversion of Logical Names" with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Mixed.

At the bottom of the dialog, there are five buttons: "< Back", "Next >", "OK" (which is highlighted with a blue border), "Cancel", and "Help".


14. Click **OK**.

## Reverse Engineering Models

The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.



## Reverse Engineering Models


---

You can edit the shape of the nodes to look like the standard table-like structure. On the ribbon, click **View > Field**. You can also change the label color, size, and caption using the Properties pane.

Along with Database, Labels, and Nodes, other objects, such as Global Indexes, Global Constraints, Users, and Roles are retrieved.




## Reverse Engineering Models



You can view these objects via the model diagram or view their properties via the Model Explorer. Right-click an object and then, click the required Properties option. For example, on the model diagram, right click a node and then, click **Node Properties**. The Neo4j Node

## Reverse Engineering Models

Editor appears. You can view the node's CREATE statement on the NoSQL tab. As seen, the node, Person has two properties, born and name to store additional information.



## Reverse Engineering Options for Neo4j

Following are the reverse engineering options for Neo4j.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or database	<b>Database:</b> Indicates that the model is reverse engineered from database  <b>Script File:</b> Indicates that the model is reverse engineered from a script
File	Specifies the script file's location	This option is available only when the Script File option is selected.

### Connection

Parameter	Description	Additional Information
Connection Method	Specifies the type of connection you want to use. Using <b>Direct</b> connects to your database directly.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted in one of the following formats: <ul style="list-style-type: none"> <li><i>Neo4j://&lt;IP address&gt;</i></li> <li><i>Neo4j+s://&lt;IP address&gt;</i></li> <li><i>bolt://&lt;IP address&gt;</i></li> </ul>	For example: <ul style="list-style-type: none"> <li><i>Neo4j://localhost</i></li> <li><i>Neo4j+s://localhost</i></li> <li><i>bolt://localhost</i></li> </ul>
Port	Specifies the port for your database based on your Hostname/IP mechanism	Default port number is 7687.



Other than the above Hostname/IP formats, Neo4j supports the Bolt+s://<IP address> format. However, erwin Data Modeler does not support it at the moment.

## Databases

Parameter	Description	Additional Information
System Objects	Specifies whether system databases are included under the Available Databases	
Available Databases	Specifies a list of available databases	
Selected Databases	Specifies a list of selected databases for reverse engineering	

## Label

Parameter	Description	Additional Information
Available Labels	Specifies a list of available labels in the selected databases	
Selected Labels	Specifies a list of selected labels for reverse engineering	

## Option Set

Parameter	Description	Additional Information
Option Set	Specifies the option set template for reverse engineering	<p><b>Open:</b> Use this option to open a saved XML option set file.</p> <p><b>Save:</b> Use this option to save the configured option set.</p> <p><b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location.</p> <p><b>Delete:</b> Use this option to delete an option set.</p>
<Option Set Name>	Specifies the objects to be reverse engineered according to the selected	

## Reverse Engineering Options for Neo4j

	option set. You can edit this list.	
--	-------------------------------------	--

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	
Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Conversion of Logical Names	Specifies how the case conversion of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

The options on this tab are available only while reverse engineering via [erwin DM Scheduler](#).

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model	When you schedule a job on a remote server, ensure the model path is same for remote and

## Reverse Engineering Options for Neo4j

	should be saved and its name	local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option. <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set. <b>Standard Default Option Set:</b> Indicates that

## Reverse Engineering Options for Neo4j

		standard metadata is included. CC works fast with this option set compared to the Advanced option set.
--	--	--

# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process. This topic walks you through the steps to forward engineer a Neo4j model. For detailed description of forward engineering options, refer to the [Forward Engineering Options](#) topic.

To forward engineer a model:

1. Open your Neo4j model.




Ensure that you are in the Physical mode.

2. Click **Actions** > **Schema**.

The Forward Engineer Schema Generation Wizard appears.



## Forward Engineering Models



3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.

## Forward Engineering Models

The screenshot shows the 'Forward Engineer Schema Generation Wizard' dialog box. The title bar reads 'Forward Engineer Schema Generation Wizard'. Below the title bar, the section is titled 'Schema Generation Options' with a subtitle: 'This page allows the user to change the Forward Engineer Schema Generation Options.' On the left, there is a sidebar with four tabs: 'Overview', 'Option Selection' (which is selected), 'Node Filter', and 'Preview'. The main area contains several configuration options:


- Option Set:** A dropdown menu showing 'Default NoSQL Schema Generation'. To its right are buttons: 'Open...', 'Save', 'Save As...', and 'Delete'.
- Database Template:** A text field containing 'Neo4j.fet'. To its right are buttons: 'Browse...', 'Edit...', and 'Reset'.
- Script Option:** A group box containing two checkboxes: 'Pre-Script' and 'Post-Script'.
- General Syntax Option:** A group box containing three checkboxes: 'Use DB' (checked), 'Create', and 'Drop'.
- Node Syntax Option:** A group box containing two checkboxes: 'Create' (checked) and 'Blank Value'.
- Global Index Syntax Option:** A group box containing two checkboxes: 'Create' (checked) and 'Drop'.
- Global Constraint Syntax Option:** A group box containing two checkboxes: 'Create' (checked) and 'Drop'.
- User and Role Syntax Option:** A group box containing four checkboxes: 'Create User' (checked), 'Drop User', 'Create Role' (checked), and 'Drop Role'.

At the bottom of the dialog, there are six buttons: '< Back', 'Next >', 'Generate', 'OK' (highlighted with a blue border), 'Cancel', and 'Help'.

4. Click **Next**.

The Node Filter section appears. It displays a list of nodes available in your model.

## Forward Engineering Models




5. Select the nodes that you want to forward engineer.

6. Click **Preview** to view the schema and its script.


The schema is available on the Viewer tab.

## Forward Engineering Models




The script is available on the Text tab.

## Forward Engineering Models




Use the following options:

- **Error Check** (

7. Click **Generate**.

The Neo4j Connection page appears.



The image shows a 'Neo4j Connection' dialog box. It has a title bar with a close button. The main area contains several fields: 'Database' (a dropdown menu showing 'Neo4j 4.3.x'), 'Authentication' (a dropdown menu showing 'Database Authentication'), 'User Name' (a text field with 'neo4j'), and 'Password' (an empty text field). Below these fields is a table with two columns: 'Parameters' and 'Value'. The table contains three rows: 'Connection Method' with value 'DIRECT', 'Hostname/IP:' with value 'bolt://localhost', and 'Port:' with value '7687'. Below the table is a section titled 'Recent Connections:' which contains a list of two entries: 'neo4j://bolt://localhost:7687 (Neo4j) using neo4j' and 'neo4j://bolt://localhost:7687 (Neo4j 4.3.x) using neo4j'. At the bottom of the dialog are four buttons: 'Connect' (highlighted with a blue border), 'Disconnect', 'Close', and 'Help'.

Parameters	Value
Connection Method	DIRECT
Hostname/IP:	bolt://localhost
Port:	7687

Recent Connections:

- neo4j://bolt://localhost:7687 (Neo4j) using neo4j
- neo4j://bolt://localhost:7687 (Neo4j 4.3.x) using neo4j


Buttons: Connect, Disconnect, Close, Help

8. Enter User Name, Password, and appropriate connection parameters to connect the required database. Then, click **Connect**. For more information on connection parameters, refer to the [connection parameters](#) topic.

The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.

For example, the following model has two nodes with five fields and six relationships. Apart from this, it has two labels and one database.

## Forward Engineering Models



On forward engineering, the following script was generated:

```
Generate Database Schema


CREATE ('Person|Person'):'Person' {
  bom: 408f
  name: "Keanu Reeves "
})
CREATE ('Movie|Movie'):'Movie' {
  tagline: "Reality is a thing of the past "
  title: "Matrix "
  released: 7117
})
CREATE ('Person|Person'):'ACTED_IN' {
  roles:[]
}->('Movie|Movie')
CREATE ('Person|Person'):'DIRECTED'-'>('Movie|Movie')
CREATE ('Person|Person'):'PRODUCED'-'>('Movie|Movie')
CREATE ('Person|Person'):'REVIEWED' {
  summary:"lorci dolor ",
  ...
}
```

☒ Stop If Failure

Save Data... OK Pause

Based on the generated schema, the graph looks as follows in your database. It has two nodes, movie (Matrix) and person (Keanu Reeves), with six relationships.

## Forward Engineering Models





## Forward Engineering Options for Neo4j

Following are the forward engineering options for Neo4j.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at an external location. <b>Delete:</b> Use this option to delete an option set.
Database Template	Specifies the database template for controlling schema generation	<b>Browse:</b> Use this option to browse and select a database template. <b>Edit:</b> Use this option to edit a template in the Template Editor. <b>Reset:</b> Use this option to reset the Database Template option.
Script Option	Specifies the script option for schema generation	<b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed
General Syntax Option	Specifies the general syntax options for schema generation	<b>Use DB:</b> Indicates whether the Use DB syntax for databases is executed <b>Create:</b> Indicates whether the Create syntax for databases is executed <b>Drop:</b> Indicates whether the Drop syntax for databases is executed
Node Syntax Option	Specifies the node syntax options for schema	<b>Create:</b> Indicates whether the Create syntax for nodes is executed

## Forward Engineering Options for Neo4j

	generation	<b>Blank Value:</b> Indicates whether the Blank Value syntax for nodes is executed. Using this creates a syntax with blank node properties instead of random values.
Global Index Syntax Option	Specifies the global index syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for global indexes is executed <b>Drop:</b> Indicates whether the Drop syntax for global indexes is executed
Global Constraint Syntax Option	Specifies the global constraint syntax options for schema generation	<b>Create:</b> Indicates whether the Create syntax for global constraints is executed <b>Drop:</b> Indicates whether the Drop syntax for global constraints is executed
User and Role Syntax Option	Specifies the user and role syntax options for schema generation	<b>Create User:</b> Indicates whether the Create syntax for users is executed <b>Drop User:</b> Indicates whether the Drop syntax for users is executed <b>Create Role:</b> Indicates whether the Create syntax for roles is executed <b>Drop Role:</b> Indicates whether the Drop syntax for roles is executed

## Node Filter

Parameter	Description	Additional Information
Nodes	Specifies the selected nodes for schema generation	
Display either Logical Names or Physical Names		<b>Physical Names:</b> Indicates that only physical names of the nodes are included in the generated schema <b>Physical Names, show owner:</b> Indicates that physical names and owners of the nodes are included in the generated schema

## Forward Engineering Options for Neo4j

		<b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the nodes are included in the generated schema. Owners of the nodes are displayed using User.
Select all of the items in the list	Use this option to select all the nodes in the list.	
Unselect all of the items in the list	Use this option to clear all the nodes.	
Select all unselected items, and unselect all selected items	Use this option to select all the unselected nodes and clear all the previously selected nodes.	

## Preview

Parameter	Description	Additional Information
Viewer	Displays the schema in the viewer editor	<b>Collapse All:</b> Use this option to collapse all the nodes. <b>Search:</b> Use this option to search a text entered in the search box. <b>Find Previous:</b> Use this option to navigate to previous search string in the search results <b>Find Next:</b> Use this option to navigate to next search string in the search result.
Text	Displays the schema in the text editor	<b>Save:</b> Use this option to save the generated schema. <b>Search:</b> Use this option to search through the generated schema. <b>Print:</b> Use this option to print the generated schema. <b>Replace:</b> Use this option to find and replace text in the generated schema. <b>Copy:</b> Use this option to copy the selected text in the

## Forward Engineering Options for Neo4j

---

		<p>schema.</p> <p><b>Text Options:</b> Use this option to edit window settings, fonts, syntax color.</p> <p><b>Git:</b> Use this option to commit the FE script to a Git repository.</p>
--	--	--


# Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.


This topic walks you through the steps to compare an Neo4j model with database.

To compare models with database:

1. Open your Neo4j model.

 Ensure that you are in the Physical mode.


For example, the following image uses a Neo4j model with three labels and nodes with relationships.



2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model section appears.


## Comparing Changes using Complete Compare



### 3. Click **Database/Script**.


By default, the Allow Demand Loading option is selected.

## Comparing Changes using Complete Compare



### 4. Click **Load**.


The New Model dialog box appears. This starts the reverse engineering process to pull a model from the database to compare.



## Comparing Changes using Complete Compare

5. Ensure that the Database is set to Neo4j. Then, click **Next**.

The Reverse Engineering Wizard appears.



6. Click **Database**. Then, click **Next**.


The Connection section appears. Use this section to connect to the database from which you want to [reverse engineer the model](#).


7. After connection is established, click **Next**.

The Databases section appears. It displays a list of available databases.




## Comparing Changes using Complete Compare




8. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click .


This moves the selected databases under Selected Databases.

## Comparing Changes using Complete Compare



9. Click **Next** and in the Label section, click . This selects all the available labels.


## Comparing Changes using Complete Compare



10. Click **Next** and in the Option Set section, keep the default configuration.
11. Click **Next** and in the Detail Options section, keep the default configuration.
12. Click **OK**.

The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.

## Comparing Changes using Complete Compare




The dialog box is titled "Right Model Selection" and has a close button (X) in the top right corner. It contains a section "Select the Right Model" with the instruction "Please select a model for the right side of complete compare." and a "Compare Level: Database" label. On the left is a dark blue sidebar with links: "Overview", "Left Model", "Right Model" (highlighted), "Type Selection", "Left Object Selection", "Right Object Selection", and "Advanced Options". The main area has a "Load From" section with radio buttons for "File", "Database / Script" (selected), and "Mart", and a checked "Allow Demand Loading" checkbox with a "Load..." button. Below is an "Open Models in Memory:" table with two columns: "Open Models" and "Location". The table lists "Model\_3" and "Model\_4". At the bottom is a checkbox "Set selected model as read only" and a row of buttons: "Load Session...", "Save Session...", "< Back", "Next >", "Compare", "Close", and "Help".

Open Models	Location
Model_3	C:\Users\...\Quest\Technical Publications ...
Model_4	neo4j://bolt://localhost:7687 (Neo4j 4.3.x) usin...

13. Click **Next** and in the Type Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



14. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



15. Click **Next** and in the Right Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

For example, the following image shows the default options.





16. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.

For example, the following image shows that the Year node is available in your model but not in the database.

## Comparing Changes using Complete Compare



Select the Year node and click . This will move the Year node to the right model (from the database). Similarly, resolve other differences.

- As differences were moved to the right model, click . This opens the forward engineering wizard.




## Comparing Changes using Complete Compare

18. Click **Option Selection** and clear all the **Drop** check boxes.

The screenshot shows the 'Forward Engineer Schema Generation Wizard' window, specifically the 'Option Selection' tab. The window has a title bar with standard OS controls. Below the title bar, the text 'Schema Generation Options' is followed by a subtitle: 'This page allows the user to change the Forward Engineer Schema Generation Options.' On the left side, there is a vertical navigation pane with four items: 'Overview', 'Option Selection' (which is highlighted with a blue background), 'Node Filter', and 'Preview'. The main area of the window contains several configuration sections. At the top, there is an 'Option Set' dropdown menu set to 'Default NoSQL Schema Generation', with buttons for 'Open...', 'Save', 'Save As...', and 'Delete'. Below this is a 'Database Template' text field containing 'Neo4j.fet', with buttons for 'Browse...', 'Edit...', and 'Reset'. The main configuration area consists of several grouped boxes, each with a title and a set of checkboxes. The 'Script Option' box contains 'Pre-Script' and 'Post-Script'. The 'General Syntax Option' box contains 'Use DB' (checked), 'Create', and 'Drop'. The 'Node Syntax Option' box contains 'Create' (checked) and 'Blank Value'. The 'Global Index Syntax Option' box contains 'Create' (checked) and 'Drop'. The 'Global Constraint Syntax Option' box contains 'Create' (checked) and 'Drop'. The 'User and Role Syntax Option' box contains 'Create User' (checked), 'Drop User', 'Create Role' (checked), and 'Drop Role'. At the bottom of the window, there is a row of buttons: '< Back', 'Next >', 'Generate', 'OK' (highlighted with a blue border), 'Cancel', and 'Help'.

19. Click **Node Filter** and select or verify the collections to be included on the forward engineering script.

## Comparing Changes using Complete Compare



20. Click **Preview** to view and verify the alter script.
21. Click **Generate** and connect to your Neo4j database.  
The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.
22. Click **OK**. Then click **Finish**.  
This closes the Resolve Differences dialog box and displays the Complete Compare wizard.
23. Click **Close**.

# Migrating Relational Models to Neo4j Models

You can convert and migrate your relational models to Neo4j models in two ways:

- [Changing the target database](#)
- [Deriving a model](#)

This topic walks you through the steps to migrate a SQL Server model to a Neo4j model.

## Migration by Changing the Target Database


To migrate by changing the target database, follow these steps:

1. Open your relational model.



Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.




## Migrating Relational Models to Neo4j Models

---

2. On the ribbon, click **Actions > Target Database** or on the status bar, click the database name.


The erwin Data Modeler -- Target Server screen appears.



The dialog box is titled "erwin Data Modeler -- Target Server". It contains the following fields and options:

- Database:** A dropdown menu with "SQL Server" selected.
- SQL Server Version:** A dropdown menu with "2016/2017" selected.
- Default SQL Server Datatype:** A dropdown menu with "char(18)" selected.
- Default Non-Key Null Option:** Two radio buttons, with "NULL" selected and "NOT NULL" unselected.
- Buttons:** "OK" and "Cancel" buttons at the bottom right.

3. In the **Database** drop-down list, select Neo4j.




The dialog box is titled "erwin Data Modeler -- Target Server". It contains the following fields and options:

- Database:** A dropdown menu with "Neo4j" selected.
- Neo4j Version:** A dropdown menu with "4.2.x" selected.
- Default Neo4j Datatype:** A dropdown menu with "String" selected.
- Default Non-Key Null Option:** Two checkboxes, with "NOT NULL" unselected and "NULL" (implied) selected.
- Buttons:** "OK" and "Cancel" buttons at the bottom right.

4. Click **OK**.

Once the conversion is complete, the existing model is migrated to a Neo4j model.

## Migrating Relational Models to Neo4j Models



In the **Objects Count** pane, note that instead of tables and columns, we now have nodes, labels, and fields. The migration process converts tables, columns, and relationships to the NoSQL format according to the database that you select.

## Migration by Deriving a Model

To migrate by deriving a model, follow these steps:


1. Open your relational model.



Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the

**Objects Count** pane, note the number of tables, columns, and relationships.



2. On the ribbon, click **Actions > Design Layers > Derive New Model**.

The Derive Model screen appears. By default, the Source Model is set to your current model.

## Migrating Relational Models to Neo4j Models

Derive Model

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level:  
Unknown

[Overview](#)  
[Source Model](#)  
**[Target Model](#)**  
[Type Selection](#)  
[Object Selection](#)  
[Naming Standards](#)

New Model Type  
☐ Logical ☐ Physical ☒ Logical/Physical

Create Using Template:  
Blank Logical/Physical Model

Remove

Browse File System...

Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

Target Database  
Database: SQL Server Version: 2016/2017  
☐ Auto Denormalization ☐ Auto Normalization ☐ Relationships

< Back

Next >

Derive

Close

Help

## Migrating Relational Models to Neo4j Models

3. In the **Database** drop-down list, select **Neo4j**.

**Derive Model** [X]

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level: Unknown

**Overview**  
**Source Model**  
**Target Model**  
**Type Selection**  
**Object Selection**  
**Naming Standards**

**New Model Type**  
☐ Logical ☐ Physical ☒ Logical/Physical

**Create Using Template:**  
Blank Logical/Physical Model

Remove Browse File System... Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

**Target Database**  
Database: Neo4j Version: 4.3.x

< Back Next > Derive Close Help

4. Click **Next**.




If the Type Resolution screen appears, click **Finish**.

The Type Selection section appears.




## Migrating Relational Models to Neo4j Models



5. Select the types of objects that you want to derive into the target Neo4j model.
6. Click **Next**.  
The Object Selection section appears. Based on the object types you selected in step 5, it displays a list of objects.

## Migrating Relational Models to Neo4j Models




7. Select the objects that you want to derive into the target Neo4j model.


8. Click **Derive**.

The model derivation process starts.


## Migrating Relational Models to Neo4j Models




Once the conversion is complete, the existing model is migrated to a Neo4j database.



In the **Objects Count** pane, note that instead of tables and columns, we now have nodes and fields. The migration process converts tables, columns, and relationships to the NoSQL format according to the database that you select.

The derived model has table-like representation. To convert it to graph-like representation, on the ribbon, go to **View > Display Level** group. Then, click . This converts the model diagram as follows:



## Parquet Support

erwin Data Modeler (DM) now supports [Parquet 2.x](#) as a target database. This implementation supports the following objects:

- Record
  - Field

Following are the supported data types:

- ARRAY
- BINARY
- BOOLEAN
- BYTE ARRAY
- DOUBLE
- FIXED LEN BYTE ARRAY
- FLOAT
- GROUP
- INT 32
- INT 64
- INT 96
- UNKNOWN

Parquet implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from script](#)
- [Forward engineering models to the file format](#)
- [Comparing changes using Complete Compare](#)
- [Migrating relational models to Parquet models](#)

# Reverse Engineering Models

You can create a Parquet data model from a script using the Reverse Engineering process.


This topic walks you through the steps to reverse engineer a Parquet model. For detailed description of reverse engineering options, refer to the [Reverse Engineering Options](#) topic.

To reverse engineer the Parquet model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.

The New Model screen appears.

2. Click **Logical/Physical** and set **Database** to **Parquet**.



New Model

Type

☐ Logical ☐ Physical ☒ Logical/Physical ☐ Match template

Target Server

☐ Match template target server

Database: Parquet Version: 2.x

Template

<Default>


☐ Preserve the template binding

Next Cancel

3. Click **Next**.

The Reverse Engineering Wizard appears.


## Reverse Engineering Models



4. Click **Script File**.
5. Click **Browse** to select the required JSON file.
6. Click **Next**.

The Detailed Options section appears.

## Reverse Engineering Models




7. Set up appropriate options based on your requirement.
8. Click **OK**

The reverse engineering process starts.

Once the process is complete, based on your selections, a schema is generated, and a model is created. For example, in the following model, four records and 206 fields are created. In the `account_string_components_15.0` record, the `city` field is nested inside the `properties` field, which is nested under another `properties` field.



## Reverse Engineering Models



## Reverse Engineering Options for Parquet

The following are the reverse engineering options for Parquet in erwin DM.

### Overview

Field	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or database	The Database option is not available for Parquet.
File	Specifies the script file location	

### Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	

## Reverse Engineering Models

Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Conversion of Logical Names	Specifies how the case conversion of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model should be saved and its name	When you schedule a job on a remote server, ensure the model path is same for remote and local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC	

## Reverse Engineering Models

	output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option. <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set. <b>Standard Default Option Set:</b> Indicates that standard metadata is included. CC works fast with this option set compared to the Advanced option set.

# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process.

This topic walks you through the steps to forward engineer a Parquet model. For detailed of forward engineering options, refer to the [Forward Engineering Options](#) topic.

To forward engineer a Parquet model:


1. Open your Parquet model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.

2. Click **Actions > Schema**.


The Forward Engineer Schema Generation Wizard appears.



3. Click **Option Selection**.

The Option Selection section displays the default option set. Select appropriate syntax


options.



4. Click **Next**.


The Record Filter section appears. It displays a list of records available in your model.

## Forward Engineering Models




5. Select the records that you want to forward engineer.

### 6. Click **Preview** to view the schema script.




Use the following options:

- **Error Check** (

### 7. Click **Generate**.

The following screen appears.



8. Use the following options:

- **Set Path:** Use this option to set the location to save the generated forward engineering script file.
- **Generate Multiple Files:** By default, a single forward engineering script file is created. Use this option to save the script into multiple files, grouped-by objects.
- **File Name Prefix:** Use this option to add a script file name. Enter a file name. If this option is not selected, the script file is saved with a default name, Erwin\_FE\_Script.json.

9. Click **Save**.

Your script file is saved in the JSON format at the configured location. You can open it in any text editor and verify.



## Forward Engineering Options for Parquet

The following are the forward engineering options for Parquet in erwin DM.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.
Database Template	Specifies the database template for controlling schema generation	<b>Browse:</b> Use this option to browse and select a database template. <b>Edit:</b> Use this option to edit a template in the Template Editor. <b>Reset:</b> Use this option to reset the Database Template option.
Script Option	Specifies the script option for the schema generation	<b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed
Comments	Indicates whether comments are included in the schema	
Hive	Indicates whether the external table syntax for Hive is executed	

### Record Filter

## Forward Engineering Options for Parquet

Parameter	Description	Additional Information
Records	Specifies the selected records for the schema generation	
Display either Logical Names or Physical Names		<b>Logical Names:</b> Indicates that only logical names of the records are included in the generated schema <b>Physical Names:</b> Indicates that only physical names of the records are included in the generated schema <b>Physical Names, show owner:</b> Indicates that physical names and owners of the records are included in the generated schema <b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the records are included in the generated schema. Owners of the records are displayed using User.
Select all of the items in the list	Use this option to select all the records in the list.	
Unselect all of the items in the list	Use this option to unselect all the records.	
Select all unselected items, and unselect all selected items	Use this option to select all the unselected records and unselect all the previously selected records.	

## Preview

Parameter	Description	Additional Information
Viewer	Displays the schema in	<b>Collapse All:</b> Use this option to collapse all the nodes.

## Forward Engineering Options for Parquet

	the viewer editor	<p><b>Search:</b> Use this option to search a text entered in the search box.</p> <p><b>Find Previous:</b> Use this option to navigate to previous search string in the search results</p> <p><b>Find Next:</b> Use this option to navigate to next search string in the search result.</p>
Text	Displays the schema in the text editor	<p><b>Save:</b> Use this option to save the generated schema.</p> <p><b>Search:</b> Use this option to search through the generated schema.</p> <p><b>Print:</b> Use this option to print the generated schema.</p> <p><b>Replace:</b> Use this option to find and replace text in the generated schema.</p> <p><b>Copy:</b> Use this option to copy the selected text in the schema.</p> <p><b>Text Options:</b> Use this option to edit window settings, fonts, and syntax color.</p> <p><b>Git:</b> Use this option to commit the FE script to a Git repository.</p>


# Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.


This topic walks you through the steps to compare a Parquet model with script.

To compare models with script:

1. Open your Parquet model.



For example, the following image uses a Parquet model with four records.



2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model section appears.

## Comparing Changes using Complete Compare

Right Model Selection

**Select the Right Model**  
Please select a model for the right side of complete compare.

Compare Level:  
Database

Load From

☒ File ☐ Database / Script ☐ Mart

Load...

Open Models in Memory:

Open Models	Location
Model_2	C:\Users\SOJha\Documents\Parquet-REDB\accoun...


☐ Set selected model as read only

Load Session... Save Session... < Back Next > Compare Close Help

### 3. Click **Database/Script**.

By default, the Allow Demand Loading option is selected.

## Comparing Changes using Complete Compare




The 'Right Model Selection' dialog box is used to select a model for the right side of a complete compare. It features a sidebar with navigation links: Overview, Left Model, Right Model (selected), Type Selection, Left Object Selection, Right Object Selection, and Advanced Options. The main area is titled 'Select the Right Model' and includes the instruction 'Please select a model for the right side of complete compare.' The 'Compare Level' is set to 'Database'. Under 'Load From', the 'Database / Script' radio button is selected, and 'Allow Demand Loading' is checked. A 'Load...' button is present. Below, the 'Open Models in Memory:' section contains a table with two columns: 'Open Models' and 'Location'. The table lists 'Model\_2' with its location as 'C:\Users\SOjha\Documents\Parquet-REDB\accoun...'. A checkbox 'Set selected model as read only' is at the bottom. The footer contains buttons for 'Load Session...', 'Save Session...', '< Back', 'Next >', 'Compare', 'Close', and 'Help'.

Open Models	Location
Model_2	C:\Users\SOjha\Documents\Parquet-REDB\accoun...

### 4. Click **Load**.

The New Model dialog box appears. This starts the reverse engineering process to pull a model from the script to compare.




The 'New Model' dialog box is used to configure a new model. It includes a 'Type' section with radio buttons for 'Logical', 'Physical', 'Logical/Physical' (selected), and 'Match template'. The 'Target Server' section has a checkbox for 'Match template target server' and dropdowns for 'Database' (set to 'Parquet') and 'Version' (set to '2.x'). The 'Template' section has a dropdown set to '<Default>' and a checkbox for 'Preserve the template binding'. 'Next' and 'Cancel' buttons are at the bottom right.

## Comparing Changes using Complete Compare

5. Ensure that the Database is set to Parquet. Then, click **Next**.

The Reverse Engineer Process Wizard appears.



6. Click **Script File**. Then, browse and select a script file.

7. Click **OK**.

The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.

## Comparing Changes using Complete Compare

Right Model Selection

**Select the Right Model**  
Please select a model for the right side of complete compare.

Compare Level:  
Database

[Overview](#)  
[Left Model](#)  
**[Right Model](#)**  
[Type Selection](#)  
[Left Object Selection](#)  
[Right Object Selection](#)  
[Advanced Options](#)

Load From  
☐ File ☒ Database / Script ☐ Mart  
☒ Allow Demand Loading [Load...](#)

Open Models in Memory:

Open Models	Location
Model_2	C:\Users\SOjha\Documents\Parquet-REDB\accoun...
Model_6	C:\Users\SOjha\Documents\Parquet-REDB\Parque...

☐ Set selected model as read only


[Load Session...](#) [Save Session...](#) [< Back](#) [Next >](#) [Compare](#) [Close](#) [Help](#)

8. Click **Next** and in the Type Selection section, select the appropriate options.



## Comparing Changes using Complete Compare


For example, the following image shows the default options.



9. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare


For example, the following image shows the default options.



10. Click **Next** and in the Right Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

For example, the following image shows the default options.





11. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and script.


For example, the following image shows that the AdventureWorks record is available in your model but not in the script.

## Comparing Changes using Complete Compare



Select the AdventureWorks record and click . This will move the AdventureWorks record to the right model. Similarly, resolve other differences.

12. As differences were moved to the right model, click . This opens the Forward Engineering Alter Script Schema Generation Wizard.
13. Click **Record Filter** and select or verify the records to be included on the forward engineering script.



14. Click **Preview** to view and verify the alter script.
15. Click **Generate**.  
The forward engineering process starts. The script generates your physical database

## Comparing Changes using Complete Compare

---

schema. You can verify the newly generated schema and save it.

16. Click **OK**. Then click **Finish**.

This closes the Resolve Differences dialog box and displays the Complete Compare wizard.

17. Click **Close**.

# Migrating Relational Models to Parquet Models

You can convert and migrate your relational models to Parquet models in two ways:

- [Changing the target database](#)
- [Deriving a model](#)

This topic walks you through the steps to migrate a SQL Server model to a Parquet model.

## Migration by Changing the Target Database


To migrate by changing the target database, follow these steps:

1. Open your relational model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.


For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.




2. On the ribbon, click **Actions > Target Database** or on the status bar, click the database name.

The erwin Data Modeler -- Target Server screen appears.

## Migrating Relational Models to Parquet Models




3. In the **Database** drop-down list, select MongoDB.  
By default, the Auto Denormalization check box is selected. Keep it selected.




4. Click **OK**.  
The conversion process starts.

## Migrating Relational Models to Parquet Models



Once the conversion is complete, the existing model is migrated to a Parquet model.



In the **Objects Count** pane, note that instead of tables and columns, we now have fields and records. Also, the Relationships count has changed to 0. The migration process converts and merges multiple tables, columns, and relationships to the NoSQL format according to the database that you select.



This migration method overwrites the existing model once you save it. Hence, we recommend that you keep a backup of your original model.

## Migration by Deriving a Model

To migrate by deriving a model, follow these steps:




## Migrating Relational Models to Parquet Models

1. Open your relational model in erwin Data Modeler (DM).



Ensure that you are in the Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.



2. On the ribbon, click **Actions > Design Layers > Derive New Model**.

The Derive Model screen appears. By default, the Source Model is set to your current model.

## Migrating Relational Models to Parquet Models

Derive Model

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level:  
Unknown

[Overview](#)  
[Source Model](#)  
**[Target Model](#)**  
[Type Selection](#)  
[Object Selection](#)  
[Naming Standards](#)

New Model Type  
☐ Logical ☐ Physical ☒ Logical/Physical

Create Using Template:  

Blank Logical/Physical Model

Remove

Browse File System...

Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

Target Database  
Database: 

SQL Server

 Version: 

2016/2017

☐ Auto Denormalization ☐ Auto Normalization ☐ Relationships

< Back

Next >

Derive

Close

Help

3. In the **Database** drop-down list, select **Parquet**.  
By default, the Auto Denormalization check box is selected. Keep it selected.

## Migrating Relational Models to Parquet Models

Derive Model

**Select the Target Model**  
Please select the options to create a new derived model

Compare Level: Unknown

[Overview](#)  
[Source Model](#)  
**Target Model**  
[Type Selection](#)  
[Object Selection](#)  
[Naming Standards](#)

New Model Type  
☐ Logic ☐ Physical ☒ Logical/Physical

Create Using Template:  
Blank Logical/Physical Model

Remove Browse File System... Browse Mart...

Creates a new model with both logical and physical levels (erwin DM classic) and default settings.

Target Database  
Database: Parquet Version: 2.x

☒ Auto Denormalization

< Back Next > Derive Close Help


- Click **Next**.



If the Type Resolution screen appears, click **Finish**.


The Type Selection section appears.

## Migrating Relational Models to Parquet Models



5. Select the types of objects that you want to derive into the target Parquet model.
6. Click **Next**.  
The Object Selection section appears. Based on the object types you selected in step 5, it displays a list of objects.

## Migrating Relational Models to Parquet Models




7. Select the objects that you want to derive into the target Parquet model.


8. Click **Derive**.

The model derivation process starts.

## Migrating Relational Models to Parquet Models



Once the conversion is complete, the existing model is migrated to a NoSQL database.



In the **Objects Count** pane, note that instead of tables and columns, we now have records and fields. Also, the Relationships count has changed to 0. The migration process converts and merges multiple tables, columns, and relationships to the NoSQL format according to the database that you select.

## Databricks Support

erwin Data Modeler (DM) now supports [Databricks](#) as a target database. This implementation supports the following objects:

## Migrating Relational Models to Parquet Models

---

- CTAS
  - CTAS Column
- Database
- Function
- Group
- Table
  - Table Column
  - Table Partition
- User Id
- View
  - View Column

The following is the list of supported data types:

- Array
- Boolean
- Double
- Integer
- Null
- Object
- String

Databricks implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)

# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process. This topic walks you through the steps to reverse engineer a Databricks model. While reverse engineering erwin Data Modeler focuses on schema generation rather than data or information.

For detailed description of reverse engineering options, refer to the [Reverse Engineering Options](#) topic.

To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to Databricks.

The screenshot shows the 'New Model' dialog box with the following settings:


- Type:** Logical (unselected), Physical (unselected), **Logical/Physical** (selected), Match template (unselected).
- Target Server:** Match template target server (checked). Database: Databricks (selected). Version: 1.0 (selected).
- Template:** <Default> (selected). Preserve the template binding (unchecked).

The 'Next' button is highlighted with a blue border.

3. Click **Next**.  
The Reverse Engineering Wizard appears.



## Migrating Relational Models to Parquet Models



4. Click one of the following options:

- **Database:** Use this option to reverse engineer a model from your database.



If you click **Database**, continue to step 5.

- **Script File:** Use this option to reverse engineer a model from a script. Selecting this option enables the File field. Click **Browse** and select the necessary script file.



If you click **Script File**, see step 13 below.

5. Click **Next**.

The Connection section appears.

# Migrating Relational Models to Parquet Models

Reverse Engineering Wizard

Connection

Configure database connection options

Overview

Connection

Databases

Tables

Option Set

Detailed Options

Scheduler

Database

Databricks

Authentication

Database Authentication

User Name

itpurchasing@quest.com

Password

Parameters	Value
Connection Type	Use ODBC Data Source
ODBC Data Source	Databricks
Invoke ODBC Administrator	<input type="checkbox"/>

Connect

Disconnect

API Connection String

Recent Connections:

(Databricks) on Databricks using itpurchasing@quest.com

< Back

Next >

OK

Cancel

Help

6. Enter your **User Name** and **Password**.

The following table explains the connection parameters:

Parameter	Description	Additional Information
Connection Type	Specifies the type of connection you want to use. Select <b>Use ODBC Data Source</b> to connect using the ODBC data source that you have defined. Select <b>Use JDBC Connection</b> to connect using JDBC.	

## Migrating Relational Models to Parquet Models

ODBC Data Source	Specifies the data source to which you want to connect. The drop-down list displays the data sources that are defined on your computer.	
Invoke ODBC Administrator	Specifies whether you want to start the ODBC Administrator software and display the Select Data Source dialog. You can then select a previously defined data source, or create a data source.	
Connection String	Specifies the connection string based on your JDBC instance in the following format:  <i>jdbc:spark://&lt;server-host-name&gt;:443/default;transportMode=http;ssl=1;httpPath=&lt;http-path&gt;</i>	This option is available only when Connection method is set to JDBC Connection.  For example, jdbc:spark://dbc-64e36c82-9e5d.cloud.databricks.com:443/default;transportMode=http;ssl=1;httpPath=sql/protocolv1/o/2132616201277612/1108-064928-9gy4v7gf

### 7. Then, Click **Connect**.

On successful connection, your connection information is displayed under Recent Connections.

# Migrating Relational Models to Parquet Models

Reverse Engineering Wizard

Connection

Configure database connection options

Overview

Connection

Databases

Tables

Option Set

Detailed Options

Scheduler

Database

Databricks

Authentication

Database Authentication

User Name

itpurchasing@quest.com

Password

.....

Parameters	Value
Connection Type	Use ODBC Data Source
ODBC Data Source	Databricks
Invoke ODBC Administrator	<input type="checkbox"/>

Connect

Disconnect

API Connection String

Recent Connections:

(Databricks) on Databricks using itpurchasing@quest.com

< >

< Back

Next >

OK


Cancel


Help


8. Click **Next**.

## Migrating Relational Models to Parquet Models

The Databases section appears. It displays a list of available databases.




9. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click .





10. Click **Next**.  
The Tables section appears. It displays a list of available tables in the databases that

## Migrating Relational Models to Parquet Models

you selected in step 9.



11. Under **Available tables**, select the tables that you want to reverse engineer. Then, click .




## Migrating Relational Models to Parquet Models

---

12. Click **Next**.


The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.



13. Click **Next**.

The Detailed Options section appears. Set up appropriate options based on your requirement.

## Migrating Relational Models to Parquet Models



The image shows a Windows-style dialog box titled "Reverse Engineering Wizard". The main title bar includes standard minimize, maximize, and close buttons. Below the title bar, the text "Reverse Engineering Wizard" is followed by a subtitle "Detailed Options" and a description "Configure detailed reverse engineering options.".

On the left side, there is a vertical sidebar with a list of steps: "Overview", "Connection", "Databases", "Label", "Option Set", "Detailed Options" (which is highlighted with a white background), and "Scheduler".

The main area of the dialog is divided into two sections. The top section is titled "NSM Options" and contains a label "Glossary CSV File:" followed by a text input field and a "Browse..." button. The bottom section is titled "Reverse Engineer" and contains two groups of radio buttons. The first group is "Case Conversion of Physical Names" with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Force. The second group is "Case Conversion of Logical Names" with options: ☒ None, ☐ lower, ☐ UPPER, and ☐ Mixed.


At the bottom of the dialog, there are five buttons: "< Back", "Next >", "OK" (which is highlighted with a blue border), "Cancel", and "Help".

14. Click **OK**.




## Migrating Relational Models to Parquet Models


The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.




Along with Databases and Tables, other objects, such as Groups, Relationships, User IDs, and Views are retrieved.



You can view these objects via the model diagram or view their properties via the Model Explorer. Right-click an object and then, click the required Properties option. For example, on the model diagram, right click a table and then, click **Table Properties**. The Databricks

## Migrating Relational Models to Parquet Models

Table Editor appears. You can view the table's CREATE statement on the SQL tab. As seen, the table, family has four columns, address, children, friends, and name.



## Reverse Engineering Options for Databricks

The following are the reverse engineering options for Databricks in erwin DM.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or database	<b>Database:</b> Indicates that the model is reverse engineered from database <b>Script File:</b> Indicates that the model is reverse engineered from a script

## Migrating Relational Models to Parquet Models

File	Specifies the script file location	This option is available when Script File is selected.



While reverse engineering from script, for the LIKE TABLE syntax, ensure that you use the USING clause.

## Connection

Parameter	Description	Additional Information
Connection Type	Specifies the type of connection you want to use. Select <b>Use ODBC Data Source</b> to connect using the ODBC data source that you have defined. Select <b>Use JDBC Connection</b> to connect using JDBC.	
ODBC Data Source	Specifies the data source to which you want to connect. The drop-down list displays the data sources that are defined on your computer.	
Invoke ODBC Administrator	Specifies whether you want to start the ODBC Administrator software and display the Select Data Source dialog. You can then select a previously defined data source, or create a data source.	
Connection	Specifies the connection string based on your JDBC instance in the following	This option is available only when Connection method is set to JDBC Connection.

## Migrating Relational Models to Parquet Models

String	format:  <i>jdbc:spark://&lt;server-host-name&gt;:443/default;transportMode= e=http;ssl=1;httpPath=&lt;http-path&gt;</i>	For example, jdbc:spark://dbc-64e36c82-9e5d.cloud.databrick-s.com:443/default;transportMode=http;ssl=1;httpPath=sql/protocolv1/o/2132616201277612/1108-064928-9gy4v7gf
--------	--	--

## Databases

Parameter	Description	Additional Information
Available Databases	Specifies a list of available databases	
Selected Databases	Specifies a list of selected databases for reverse engineering	
System Objects	Specifies whether system databases are included under the Available Databases	

## Tables

Parameter	Description	Additional Information
Available Tables	Specifies a list of available tables	
Selected Tables	Specifies a list of selected tables for reverse engineering	

## Option Sets

Parameter	Description	Additional Information
Option Set	Specifies the option set template for	<b>Open:</b> Use this option to open a saved

## Migrating Relational Models to Parquet Models

	reverse engineering	<p>XML option set file.</p> <p><b>Save:</b> Use this option to save the configured option set.</p> <p><b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location.</p> <p><b>Delete:</b> Use this option to delete an option set.</p>
<Option Set Name>	Specifies the objects to be reverse engineered according to the selected option set. You can edit this list.	

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	
Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<p><b>None:</b> Indicates that the case in the script file is preserved</p> <p><b>lower:</b> Indicates that the names are converted to lower case</p> <p><b>UPPER:</b> Indicates that the names are converted to upper case</p> <p><b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.</p>
Case Conversion of Logical	Specifies how the case con-	<p><b>None:</b> Indicates that the case in the script file is preserved</p> <p><b>lower:</b> Indicates that the names are converted to lower case</p>

## Migrating Relational Models to Parquet Models

Names	version of logical names is handled	<b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved
-------	-------------------------------------	---

## Scheduler

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model should be saved and its name	When you schedule a job on a remote server, ensure the model path is same for remote and local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.

## Migrating Relational Models to Parquet Models

Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option. <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set. <b>Standard Default Option Set:</b> Indicates that standard metadata is included. CC works fast with this option set compared to the Advanced option set.

## Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process. This topic walks you through the steps to forward engineer a Databricks model. For detailed description of forward engineering options, refer to the [Forward Engineering Options](#) topic.

To forward engineer a model:

1. Open your Databricks model.




Ensure that you are in the Physical mode.

2. Click **Actions** > **Schema**.

The Forward Engineer Schema Generation Wizard appears.




## Migrating Relational Models to Parquet Models



### 3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.


## Migrating Relational Models to Parquet Models



4. Click **Next**.

The Summary section appears. It displays a list of selected options for the schema generation. Use Edit Options to update selected options.


## Migrating Relational Models to Parquet Models



5. Click **Next**.

The Owner Override section appears. It displays a list of objects.


\_\_\_\_\_



6. Enter database names as owner of the objects.
7. Click **Next**.


The Table Filter section appears. It displays a list of tables available in your model.

## Migrating Relational Models to Parquet Models



8. Click **Preview** to view the schema and its script.

## Migrating Relational Models to Parquet Models




Use the following options:

- **Save** (📁): Use this option to save the generated script.
- **Print** (🖨️): Use this option to print the generated schema.
- **Search** (🔍): Use this option to search through the generated schema.
- **Copy** (📋): Use this option to copy the selected text in the schema.
- **Replace** (🔄): Use this option to find and replace text in the generated schema.
- **Text Options** (🎨): Use this option to configure the preview text editor's look and feel, such as window, font, syntax color settings. For more information, refer to the Forward Engineering Wizard - Preview Editor topic.

9. Click **Generate**.

The Databricks Connection page appears.



The image shows a 'Databricks Connection' dialog box. It has a title bar with a close button. The main area contains several fields: 'Database' (a dropdown menu with 'Databricks' selected), 'Authentication' (a dropdown menu with 'Database Authentication' selected), 'User Name' (a text field with a masked password), and 'Password' (a text field with a masked password). Below these fields is a table with two columns: 'Parameters' and 'Value'. The table has three rows: 'Connection Type' with value 'Use ODBC Data Source', 'ODBC Data Source' with value 'Databricks', and 'Invoke ODBC Administrator' with a checkbox. Below the table is a section titled 'Recent Connections:' with a list box containing one entry: '(Databricks) on Databricks using [masked]'. At the bottom of the dialog are four buttons: 'Connect' (highlighted with a blue border), 'Disconnect', 'Close', and 'Help'.


Parameters	Value
Connection Type	Use ODBC Data Source
ODBC Data Source	Databricks
Invoke ODBC Administrator	<input type="checkbox"/>

10. Enter User Name, Password, and appropriate connection parameters to connect the required database. Then, click **Connect**. For more information on connection parameters, refer to the [connection parameters](#) topic.

The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.

For example, the following model has one database, eight tables with 61 columns and seven relationships. Apart from this, it has eight indexes.

## Migrating Relational Models to Parquet Models




On forward engineering, the following script was generated:

```
1  
2 CREATE DATABASE erwin  
3 LOCATION 'dbfs:/user/hive/warehouse/erwin.db'  
4 WITH DBPROPERTIES ();  
5  
6 CREATE TABLE cust  
7 (  
8     CUST_address string,  
9     CUST_city string,  
10    CUST_first_name string,  
11    CUST_last_name string,  
12    CUST_state string,  
13    CUST_zip_code int,  
14    email string,  
15    CUST_number int  
16 )
```

Based on the generated schema, the erwin database has eight tables with 61 columns.



## Migrating Relational Models to Parquet Models



## Forward Engineering Options for Databricks

The following are the forward engineering options for Databricks in erwin DM.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.
Schema	Specifies the schema options for the schema generation	<b>Pre-Script:</b> Indicates whether the pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed

## Migrating Relational Models to Parquet Models

		<p><b>Create:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.</p> <p><b>Drop:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Drop node executes the drop syntax for that object.</p>
Table	Specifies the table options for the schema generation	<p><b>Pre-Script:</b> Indicates whether the pre-scripts attached to tables are executed</p> <p><b>Post-Script:</b> Indicates whether the post-scripts attached to tables are executed</p> <p><b>Create:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.</p> <p><b>Drop:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.</p>
Column	Specifies the column options for the schema generation	<p><b>Column CHECK:</b> Indicates whether validation rules attached to columns is included in the schema</p> <p><b>Label:</b> Indicates whether labels attached to columns are included in the schema</p> <p><b>Physical Order:</b> Indicates whether physical order attached to columns are included in the schema</p> <p><b>Default Value:</b> Indicates whether default values of the columns are included in the schema</p>
CTAS	Specifies the CTAS options for the schema generation	<p><b>Pre-Script:</b> Indicates whether the pre-scripts attached to CTAS are executed</p> <p><b>Post-Script:</b> Indicates whether the post-scripts attached to CTAS are executed</p> <p><b>Create:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the</p>

## Migrating Relational Models to Parquet Models

		Create node executes the create syntax for that object.  <b>Drop:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.
View	Specifies the View options for the schema generation	<b>Pre-Script:</b> Indicates whether the pre-scripts attached to Views are executed  <b>Post-Script:</b> Indicates whether the post-scripts attached to Views are executed  <b>Create:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.  <b>Drop:</b> Indicates whether the Create syntax for the selected objects are executed. Selecting an object under the Create node executes the create syntax for that object.
Other Options	Specifies the other options for the schema generation	Selecting an object includes it in the schema

## Summary

Parameter	Description	Additional Information
Summary	Specifies the summary of the options selected for the schema generation	<b>Show Selected Only:</b> Use this option to show the selected options only.  <b>Edit Options:</b> Use this option to edit the selected options for the schema generation.
Comment	Use this option to add comments about the schema.	

## Owner Override

Parameter	Description	Additional Inform-
-----------	-------------	--------------------

## Migrating Relational Models to Parquet Models

		ation
Object Name	Specifies the object names	
Owner Override	Specifies database as the owner of the object	

### Table Filter

Parameter	Description	Additional Information
Table	Specifies the selected tables for the schema generation	
Display either Logical Names or Physical Names		<b>Logical Names:</b> Indicates that only logical names of the tables are included in the generated schema <b>Physical Names:</b> Indicates that only physical names of the tables are included in the generated schema <b>Physical Names, show owner:</b> Indicates that physical names and owners of the tables are included in the generated schema <b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the tables are included in the generated schema. Owners of the tables are displayed using User.
Select all of the items in the list	Use this option to select all the tables in the list.	
Unselect all of the items in the list	Use this option to unselect all the tables.	
Select all unselected items, and unselect all selected	Use this option to select all the unselected tables and unselect all the previously selected tables.	

## Migrating Relational Models to Parquet Models

items		
-------	--	--

### Preview

Description	Additional Information
Displays the schema in the text editor	<p><b>Save:</b> Use this option to save the generated schema.</p> <p><b>Search:</b> Use this option to search through the generated schema.</p> <p><b>Print:</b> Use this option to print the generated schema.</p> <p><b>Replace:</b> Use this option to find and replace text in the generated schema.</p> <p><b>Copy:</b> Use this option to copy the selected text in the schema.</p> <p><b>Text Options:</b> Use this option to edit window settings, fonts, and syntax color.</p> <p><b>Git:</b> Use this option to commit the FE script to a Git repository.</p>

## Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.

This topic walks you through the steps to compare a Databricks model with database.

To compare models with database:


1. Open your Databricks model.



Ensure that you are in the Physical mode.

## Migrating Relational Models to Parquet Models

For example, the following image uses a Databricks model with eight tables, 61 columns, and seven relationships.



### 2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model section appears.

## Migrating Relational Models to Parquet Models

Right Model Selection


**Select the Right Model**  
Please select a model for the right side of complete compare.

Compare Level:  
Database

[Overview](#)  
[Left Model](#)  
**[Right Model](#)**  
[Type Selection](#)  
[Left Object Selection](#)  
[Right Object Selection](#)  
[Advanced Options](#)

Load From  
☒ File ☐ Database / Script ☐ Mart  
[Load...](#)

Open Models in Memory:

Open Models	Location
 Model_2	C:\Users\SOjha\Documents\Databricks\erwin.er...


☐ Set selected model as read only

[Load Session...](#) [Save Session...](#) [< Back](#) [Next >](#) [Compare](#) [Close](#) [Help](#)

3. Click **Database/Script**.

By default, the Allow Demand Loading option is selected.

## Migrating Relational Models to Parquet Models



Right Model Selection

**Select the Right Model**  
Please select a model for the right side of complete compare.

Compare Level:  
Database

[Overview](#)  
[Left Model](#)  
**[Right Model](#)**  
[Type Selection](#)  
[Left Object Selection](#)  
[Right Object Selection](#)  
[Advanced Options](#)

Load From  
☐ File ☒ Database / Script ☐ Mart  
☒ Allow Demand Loading [Load...](#)

Open Models in Memory:


Open Models	Location
Model_2	C:\Users\SOjha\Documents\Databricks\erwin.er...

☐ Set selected model as read only

[Load Session...](#) [Save Session...](#) [< Back](#) [Next >](#) [Compare](#) [Close](#) [Help](#)

### 4. Click **Load**.

The New Model dialog box appears. This starts the reverse engineering process to pull a model from the database to compare.



New Model

Type  
☐ Logical ☐ Physical ☒ Logical/Physical ☐ Match template

Target Server  
☐ Match template target server  
Database: [Databricks](#) Version: [\[Version\]](#)

Template  
[<Default>](#) [\[Icon\]](#) [\[Icon\]](#)

☐ Preserve the template binding

[Next](#) [Cancel](#)




## Migrating Relational Models to Parquet Models

---


5. Ensure that the Database is set to Databricks. Then, click **Next**.


The Reverse Engineer Wizard appears.




6. Click **Database**. Then, click **Next**.  
The Connection section appears. Use this section to connect to the database from which you want to [reverse engineer the model](#).
7. After connection is established, click **Next**.  
The Databases section appears. It displays a list of available databases.


## Migrating Relational Models to Parquet Models




8. Under **Available Databases**, select the databases that you want to reverse engineer. Then, click . This moves the selected databases under Selected Databases.

## Migrating Relational Models to Parquet Models



9. Click **Next** and in the Tables section, click . This selects all the available tables.

## Migrating Relational Models to Parquet Models



10. Click **Next** and in the Option Set section, keep the default configuration.
11. Click **Next** and in the Detailed Options section, keep the default configuration.
12. Click **OK**.  
The reverse engineering process starts. Once the process is complete, the Right Model is set to the one that you reverse engineered.

## Migrating Relational Models to Parquet Models

Right Model Selection


**Select the Right Model**  
Please select a model for the right side of complete compare.

Compare Level:  
Database

[Overview](#)  
[Left Model](#)  
**[Right Model](#)**  
[Type Selection](#)  
[Left Object Selection](#)  
[Right Object Selection](#)  
[Advanced Options](#)

Load From  
☒ File ☐ Database / Script ☐ Mart  
[Load...](#)

Open Models in Memory:

Open Models	Location
 Model_2	C:\Users\S0jha\Documents\Databricks\erwin.er...

☐ Set selected model as read only


[Load Session...](#) [Save Session...](#) [< Back](#) [Next >](#) [Compare](#) [Close](#) [Help](#)

13. Click **Next** and in the Type Selection section, select the appropriate options.

## Migrating Relational Models to Parquet Models

---


For example, the following image shows the default options.



14. Click **Next** and in the Left Object Selection section, select the appropriate options.

## Migrating Relational Models to Parquet Models

For example, the following image shows the default options.




15. Click **Next** and in the Right Object Selection section, select the appropriate options.

## Migrating Relational Models to Parquet Models

---

For example, the following image shows the default options.




16. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.


For example, the following image shows that the purchasinghistory table is available in your model but not in the database.



## Migrating Relational Models to Parquet Models




Select the purchasinghistory table and click . This will move the purchasinghistory table to the right model (from the database). Similarly, resolve other differences.

17. As differences were moved to the right model, click . This launches the Forward Engineering Alter Script Generation Wizard.


## Migrating Relational Models to Parquet Models

18. Click **Option Selection** and clear all the **Drop** check boxes.



19. Click **Table Filter** and select or verify the tables to be included on the forward engineering script.

## Migrating Relational Models to Parquet Models



20. Click **Preview** to view and verify the alter script.
21. Click **Generate** and connect to your Databricks database.  
The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.
22. Click **OK**. Then click **Finish**.  
This closes the Resolve Differences dialog box and displays the Complete Compare wizard.
23. Click **Close**.

# DynamoDB Support

erwin Data Modeler (DM) now supports [DynamoDB](#) as a target database. This implementation supports the following objects:

- Table
  - Item
  - Index

Following are the supported data types:

- STRING
- STRINGSET
- NUMBER
- NUMBERSET
- BINARY
- BINARYSET
- BOOLEAN
- LIST
- MAP
- NULL

DynamoDB implementation supports all erwin DM features and functions. The following sections walk you through these features:

- [Reverse engineering models from database and script](#)
- [Forward engineering models to database](#)
- [Comparing changes using Complete Compare](#)
- [Converting relational models to DynamoDB models](#)


# Reverse Engineering Models

You can create a data model from a database or a script using the Reverse Engineering process.

This topic walks you through the steps to reverse engineer a DynamoDB model. For detailed information of each reverse engineering option, refer to the [Reverse Engineering Options](#) topic.

To reverse engineer a model:

1. In erwin Data Modeler (DM), click **Actions > Reverse Engineer**.  
The New Model screen appears.
2. Click **Logical/Physical** and set **Database** to DynamoDB.




The screenshot shows the 'New Model' dialog box with the following settings:

- Type:** Logical/Physical (selected)
- Target Server:** Match template target server (unchecked), Database: DynamoDB, Version: (empty)
- Template:** <Default> (selected), Preserve the template binding (unchecked)

3. Click **Next**.  
The Reverse Engineer Process Wizard appears.

## Reverse Engineering Models



4. Click one of the following options:

- **Database:** Use this option to reverse engineer a model from a database.



If you click **Database**, continue to step 5.

- **AWS CLI Script** or **Python Script:** Use this option to reverse engineer a model from a script. You can either use AWS CLI Script or Python Script option for reverse engineering a model. Selecting this option enables the **File** field. Click **Browse** and select the a script file from your directory.



If you click **AWS CLI Script** or **Python Script**, go to step 11 to set detailed options for reverse engineering.

## Reverse Engineering Models

5. Click **Next**.

The Connection section appears.

Reverse Engineering Wizard

**Connection**  
Configure database connection options

Overview  
**Connection**  
Tables  
Option Set  
Detailed Options  
Scheduler

Database: DynamoDB  
Authentication: Database Authentication  
User Name:   
Password:   
  

Parameters	Value
Connection Method	DIRECT (CLOUD)
Access Key Id	AKIAWL6SKBGUTJYDBLWB
Secret Access Key	A6wfh9OIFMy1k/vre395uRQWngUed9pUqQR1jbr...
Region	us-east-2

Connect Disconnect API Connection String

Recent Connections:

cloud.dynamodb:AKIAWL6SKBGUTJYDBLWB:A6wfh9OIFMy1k/vre395uRQWngUed9pUqQR1jbr...

< >

< Back Next > OK Cancel Help

6. Enter your **User Name** and **Password**.

The following table explains the connection parameters.

Parameter	Description	Additional Details
Connection Method	Specifies the type of connection you want to use. Select <b>DIRECT (CLOUD)</b> to connect to a database on a cloud. Or, select <b>DIRECT (LOCAL)</b> to	

## Reverse Engineering Models

	connect to a local database.	
Hostname/IP	Specifies the host-name or IP address of the server where your database is hosted in the following format: <a href="http://localhost">http://localhost</a>	This option is available when Connection Method is set to DIRECT (LOCAL).
Port	Specifies the port configured for your database	For example, <i>9142</i> . This option is available when Connection Method is set to DIRECT (LOCAL).
Access Key ID	Specifies access key id for connecting to a database on cloud	For example: <i>AKIAI00EXAMPLE56OSFODNN7</i> This option is available when Connection Method is set to DIRECT (CLOUD).
Secret Access Key	Specifies access key for authenticating the database connection	For example: <i>FEwJalrnMDMI/K7ENGXUt/EXAMPLEKEY/b1xwfiCu</i> This option is available when Connection Method is set to DIRECT (CLOUD).
Region	Specifies the location of the remote database	This option is available when Connection Method is set to DIRECT (CLOUD).

7. Click **Connect**.


On successful connection, your connection information is displayed under Recent Connections.


8. Click **Next**.




## Reverse Engineering Models

The Tables section appears. It displays a list of available tables.




9. Under **Available Tables**, select the tables that you want to reverse engineer. Then, click .




## Reverse Engineering Models

This moves the selected tables under Selected Tables.



10. Click **Next**.


The Option Set section appears. It displays the default option set. You can either use the default or a custom option set.



11. Click **Next**.

The Detail Options section appears. Set up appropriate options based on your

requirement.




The image shows a screenshot of the 'Reverse Engineering Wizard' dialog box, specifically the 'Detailed Options' step. The window title is 'Reverse Engineering Wizard'. The subtitle is 'Detailed Options' with the instruction 'Configure detailed reverse engineering options.' On the left is a vertical sidebar with navigation links: 'Overview', 'Connection', 'Tables', 'Option Set', 'Detailed Options' (which is highlighted), and 'Scheduler'. The main area is divided into two sections. The top section, 'NSM Options', contains a 'Glossary CSV File:' label followed by a text input field and a 'Browse...' button. The bottom section, 'Reverse Engineer', contains two groups of radio buttons. The first group, 'Case Conversion of Physical Names', has four options: 'None' (selected), 'lower', 'UPPER', and 'Force'. The second group, 'Case Conversion of Logical Names', has four options: 'None' (selected), 'lower', 'UPPER', and 'Mixed'. At the bottom of the dialog are five buttons: '< Back', 'Next >', 'OK' (highlighted with a blue border), 'Cancel', and 'Help'.

12. Click **OK**.


## Reverse Engineering Models

---

The reverse engineering process starts.



Once the process is complete, based on your selections, a schema is generated and a model is created.




You can edit the shape of the nodes to look like the standard table-like structure. On the ribbon click **View > Field**. You can also change label color, size, and caption using the properties pane.

## Reverse Engineering Models

---


Along with Tables, other object such as Indexes and Items are also retrived.



You can view these objects via the model diagram or view their properties via the Model Explorer. Right-click an object and then, click the required Properties option. For example, on the model diagram, right click a table and then, click Table Properties. The DynamoDB

Reverse Engineering Models

Table Editor appears. You can view the table's property on a model.



## Reverse Engineering Options for DynamoDB

The following are the reverse engineering options for DynamoDB in erwin DM.

### Overview

Parameter	Description	Additional Information
Reverse Engineer From	Specifies whether you want to reverse engineer from a script or database	<b>Database:</b> Indicates that the model is reverse engineered from a remote or local database <b>AWS CLI Script:</b> Indicates that the model is reverse engineered from a Command Line Interface (CLI) script <b>Python Script:</b> Indicates that the model is reverse engineered from a python script
File	Specifies the script file location	This option is available when Script File is selected.

### Connection

Parameter	Description	Additional Details
Connection Method	Specifies the type of connection you want to use. Select <b>DIRECT (CLOUD)</b> to connect to a database on a cloud. Or, select <b>DIRECT (LOCAL)</b> to connect to a local database.	
Hostname/IP	Specifies the hostname or IP address of the server where your database is hosted in the following format: <a href="http://localhost">http://localhost</a>	This option is available when Connection Method is set to DIRECT (LOCAL).
Port	Specifies the port con-	For example, 9142.

## Reverse Engineering Options for DynamoDB

	figured for your database	This option is available when Connection Method is set to DIRECT (LOCAL).
Access Key ID	Specifies access key id for connecting to a database on cloud	For example: <i>AKIAI00EXAMPLE56OSFODNN7</i> This option is available when Connection Method is set to DIRECT (CLOUD).
Secret Access Key	Specifies access key for authenticating the database connection	For example: <i>FEwJalrnMDMI/K7ENGXUt/EXAMPLEKEY/b1xwfiCu</i> This option is available when Connection Method is set to DIRECT (CLOUD).
Region	Specifies the location of the remote database	This option is available when Connection Method is set to DIRECT (CLOUD).

## Tables

Parameter	Description	Additional Information
Available Tables	Specifies a list of available tables	
Selected Tables	Specifies a list of selected tables for reverse engineering	

## Option Sets

Parameter	Description	Additional Information
Option Set	Specifies the option set template for reverse engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save the configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at some external location. <b>Delete:</b> Use this option to delete an option set.



## Reverse Engineering Options for DynamoDB

<Option Set Name>	Specifies the objects to be reverse engineered according to the selected option set. You can edit this list.	
-------------------	--	--

## Detailed Options

Parameter	Description	Additional Information
NSM Options	Specifies the naming standard glossary file in the .CSV format	
Case Conversion of Physical Names	Specifies how the case conversion of physical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Force:</b> Indicates whether the physical name property of all the logical/physical models is overridden. If this option is enabled, the logical/physical link is broken between the logical and physical name. If this option is not enabled, all logical and physical names are set to the same value after the process completes.
Case Conversion of Logical Names	Specifies how the case conversion of logical names is handled	<b>None:</b> Indicates that the case in the script file is preserved <b>lower:</b> Indicates that the names are converted to lower case <b>UPPER:</b> Indicates that the names are converted to upper case <b>Mixed:</b> Indicates that the mixed-case logical names are preserved

## Scheduler

Parameter	Description	Additional Information
Model	Specifies the location where the reverse engineered model	When you schedule a job on a remote server, ensure the model path is same for remote and

## Reverse Engineering Options for DynamoDB

	should be saved and its name	local server. For example: C:\Scheduler\<Model Name>.erwin
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.
Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option.  <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set.  <b>Standard Default Option Set:</b> Indicates that

Reverse Engineering Options for DynamoDB

		standard metadata is included. CC works fast with this option set compared to the Advanced option set.
--	--	--

# Forward Engineering Models

You can generate a physical database schema from a physical model using the Forward Engineering process.

This topic walks you through the steps to forward engineer an DynamoDB model. For detailed information of each forward engineering option, refer to the [Forward Engineering Options](#) topic.

To forward engineer a DynamoDB model:

1. Open your DynamoDB model in erwin Data Modeler (DM).




Ensure that you are in the Physical mode.

2. Click **Actions > Schema**.

The Forward Engineer Schema Generation Wizard appears.

## Forward Engineering Models



### 3. Click **Option Selection**.

The Option Selection section displays the default option set. Clear the **Drop** check boxes and select other syntax check boxes as required.

## Forward Engineering Models

The screenshot shows the 'Forward Engineer Schema Generation Wizard' window, specifically the 'Schema Generation Options' tab. The window has a sidebar on the left with 'Overview', 'Option Selection' (selected), 'Table Filter', and 'Preview'. The main area contains various configuration options:


- Option Set:** A dropdown menu set to 'Default NoSQL Schema Generation'. Buttons: 'Open...', 'Save', 'Save As...', 'Delete'.
- Database Template:** A text field containing 'DynamoDB.fet'. Buttons: 'Browse...', 'Edit...', 'Reset'.
- Script Option:** Two checkboxes: 'Pre-Script' and 'Post-Script'.
- General Syntax Option:** Two checkboxes: 'AWS CLI Script' (checked) and 'Python Script'.
- Create Table Option:** Four checkboxes: 'Create' (checked), 'Drop', 'Insert' (checked), and 'Blank Value'.
- Replica Option:** Two checkboxes: 'Create' and 'Drop'.
- Index Option:** A group box containing 'GSI' with 'Create' (selected) and 'Update' radio buttons, and a 'Drop GSI' checkbox.
- Other Options:** A checkbox for 'Comments'.
- Include End Point URL:** A checkbox, followed by 'Hostname/IP:' and 'Port:' text labels with corresponding input fields.

At the bottom, there are navigation buttons: '< Back', 'Next >', 'Generate', 'OK' (highlighted with a blue border), 'Cancel', and 'Help'.

4. Click **Next**.


The Table Filter section appears. It displays a list of tables available in your model.

## Forward Engineering Models



5. Select the tables that you want to forward engineer.

### 6. Click **Preview** to view the schema script.




Use the following options:

- **Copy** (📄): Use this option to copy the script.
- **Save** (💾): Use this option to save the generated script into a single or multiple files in the TXT format.
- **Search** (🔍): Use this option to search through the generated schema.
- **Print** (🖨️): Use this option to print the generated schema.
- **Replace** (🔄): Use this option to find and replace in the generated schema.




## Forward Engineering Models

- **Text Options** (

### 7. Click **Generate**.

The DynamoDB Connection editor appears.



Parameters	Value
Connection Method	DIRECT (CLOUD)
Access Key Id	AKIAWLGSXBGUT7YDBLWB
Secret Access Key	A6wfh90SPMySk/vre395uRQW1u
Region	us-east-2


Recent Connections:

- cloud.dynamodb:AKIAWLGSXBGUT7YDBLWB:A6wfh90SPMySk/vre...



Generating forward engineering script for DynamoDB is not executed as expected and displays error, when you click Generate. Use one of the following method to generate DynamoDB script:

- ♦ Save the script and execute the file using a command line.
- ♦ Select and execute one statement at a time to generate script. For example, in the below image, one is selected from two statements in the script.




8. Enter username, password, and appropriate connection parameters to connect the required database. Then, click **Connect**.

The objects move to a database entered on the DynamoDB Connection page irrespective of the databases entered on the object editor pages. If you want to move objects to databases as entered on object editors page then do not enter any database on the DynamoDB Connection page.

## Forward Engineering Models

The forward engineering process starts. The script generates your physical database schema. You can access your database and verify the newly generated schema.



## Forward Engineering Options for DynamoDB

Following are the forward engineering options for DynamoDB.

### Option Selection

Parameter	Description	Additional Information
Option Set	Specifies the option set template for forward engineering	<b>Open:</b> Use this option to open a saved XML option set file. <b>Save:</b> Use this option to save a configured option set. <b>Save As:</b> Use this option to save an option set either in the model or in the XML format at an external location. <b>Delete:</b> Use this option to delete an option set.
Database Template	Specifies the database template for controlling schema generation	<b>Browse:</b> Use this option to browse and select a database template. <b>Edit:</b> Use this option to edit a template in the Template Editor. <b>Reset:</b> Use this option to reset the Database Template option.
Script Option	Specifies the script option for schema generation	<b>Pre-Script:</b> Indicates whether pre-scripts attached to the schema are executed <b>Post-Script:</b> Indicates whether the post-scripts attached to the schema are executed
General Syntax Option	Specifies the syntax options for schema generation	<b>AWS CLI:</b> Indicates whether the AWS CLI syntax for databases is executed

## Forward Engineering Options for DynamoDB

		<b>Python:</b> Indicates whether the Python syntax for databases is executed
Create Table Option	Specifies the table options for schema generation	<b>Create:</b> Indicates whether the create syntax for tables is executed <b>Drop:</b> Indicates whether the drop syntax for tables is executed <b>Insert:</b> Indicates whether to include fields in respective table in the schema <b>Blank Value:</b> Indicates whether to replace the random values in a field with a blank value
BackUp Table Option	Specifies the back up table options for schema generation	<b>Create:</b> Indicates whether the create syntax for tables is executed <b>Drop:</b> Indicates whether the drop syntax for tables is executed <b>Create Continuous BackUps:</b> Indicates whether to create continuous back up of the tables
Replica Option	Specifies the replica options for schema generation	<b>Create:</b> Indicates whether the create syntax for tables is executed <b>Drop:</b> Indicates whether the drop syntax for tables is executed
GSI	Specifies whether the Global Secondary Index (GSI) option is enabled for schema generation. Use one of the following options:  <b>Create:</b> Specifies to create GSI for the new and existing tables during schema generation	<b>Drop GSI:</b> Indicates whether the Drop syntax for GSI is executed

## Forward Engineering Options for DynamoDB

	<b>Update:</b> Specifies to create GSI using update statement for a tables during schema generation	
Comments	Indicates whether comments are included in the schema	
Include End Point URL	Specifies whether to include end point URL information such as hostname and port number in the script during schema generation	

## Table Filter

Parameter	Description	Additional Information
Tables	Specifies the selected tables for schema generation	
Display either Logical Names or Physical Names	Specifies the database template for controlling schema generation	<b>Logical Names:</b> Indicates that only logical names of the tables are included in the generated schema  <b>Physical Names:</b> Indicates that only physical names of the tables are included in the generated schema  <b>Physical Names, show owner:</b> Indicates that physical names and owners of the tables are included in the generated schema  <b>Physical Names, show owner using User:</b> Indicates that the physical names and owners of the tables are included in the generated schema. Owners of the tables are displayed using User.
Select all of the items in the list	Use this option to select all the tables in the list.	
Unselect all of the items in	Use this option to clear all the tables.	

## Forward Engineering Options for DynamoDB

the list		
Select all unselected items, and unselect all selected items	Use this option to select all the unselected tables and clear all the previously selected tables.	

## Preview

Parameter	Description	Additional Information
Text	Displays the schema in the text editor	<b>Save:</b> Use this option to save the generated schema into single or multiple files. <b>Search:</b> Use this option to search through the generated schema. <b>Print:</b> Use this option to print the generated schema. <b>Replace:</b> Use this option to find and replace text in the generated schema. <b>Copy:</b> Use this option to copy the selected text in the schema. <b>Text Options:</b> Use this option to edit window settings, fonts, syntax color. <b>Error Check:</b> Use this option to view error report for the generated schema. <b>Git:</b> Use this option to commit the FE script to a Git repository.

# Comparing Changes using Complete Compare

You can compare your model with database, script, or another local model to check for differences using the Complete Compare wizard. Based on the results, you can then resolve or merge differences. Thus, maintaining a consistent model and database.

This topic walks you through the steps to compare a DynamoDB model with database.


To compare models with database:

1. Open your DynamoDB model in erwin Data Modeler (DM).



Ensure that you are in Physical mode.

For example, the following image uses a DynamoDB model with 11 tables.




2. Click **Actions > Complete Compare**.

By default, the Complete Compare wizard assigns the open model as the Left Model. Hence, the Right Model Section appears.




## Comparing Changes using Complete Compare



3. Click **Database/Script**.

By default, the Allow Demand Loading option is selected.




4. Click **Load**.

The New Model dialog box appears. This starts the reverse engineering process to pull


## Comparing Changes using Complete Compare

a model from the database to compare.



5. Ensure that the Database is set to the correct one. In this case, DynamoDB. Then, click **Next**.

The Reverse Engineer Wizard appears.



6. Click **Database**. Then, click **Next**.


The Connection section appears. Use this section to connect to the database from


## Comparing Changes using Complete Compare

which you want to [reverse engineer the model](#).


7. After the connection is established, click **Next**.

The Tables section appears. It displays a list of available tables.



8. Under **Available Tables**, select the tables that you want to reverse engineer. Then, click .

This moves the tables under Selected Tables.




9. Click **Next** and in the Option Set section, keep the default configuration.
10. Click **Next** and in the Detail Options section, keep the default configuration.
11. Click **OK**.

The reverse engineering process starts. Once the process is complete, the Right Model


## Comparing Changes using Complete Compare

is set to the one that you reverse engineered.



12. Click **Next** and in the Type Selection section, select the appropriate options.

For example, the following image shows the default options.




## Comparing Changes using Complete Compare

---

13. Click **Next** and in the Left Object Selection section, select the appropriate options.

For example, the following image shows the default options.




14. Click **Next** and in the Right Object Selection section, select the appropriate options.

## Comparing Changes using Complete Compare

---

For example, the following image shows the default options.





15. Click **Compare**.


The comparison process runs, and the Resolve Differences dialog box appears. It displays the differences between your model and database.

For example, the following image shows that the GameScores table is available in your model but not in the database.

## Comparing Changes using Complete Compare




Select the missing table and click . This will move the GameScores table to the right model (from the database). Similarly, resolve other differences.


- As differences were moved to the right model, click .  
This launches the Forward Engineering Alter Script Generation Wizard.

## Comparing Changes using Complete Compare

- Click **Option Selection** and clear all the **Drop** check boxes.



- Click **Table Filter** and select or verify the tables to be included on the forward engineering script.



- Click **Preview** to view and verify the alter script.
- Click **Generate** and connect to your DynamoDB.  
The forward engineering process starts. The script generates your physical database



## Comparing Changes using Complete Compare

---

schema. You can access your database and verify the newly generated schema.

21. Click **OK**. Then click **Finish**.

This closes the Resolve Differences dialog box and displays the Complete Compare wizard.

22. Click **Close**.

# Migrating Relational Models to DynamoDB Models

You can migrate your relational models to DynamoDB models in two ways:

- [Changing the target database](#)
- [Deriving a model](#)

This topic walks you through the steps to migrate a SQL Server model to a DynamoDB model.

## Migration by Changing the Target Database


To migrate by changing the target database, follow these steps:

1. Open your relational model in erwin Data Modeler (DM).



Ensure that you are in Physical mode.


For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.




2. On the ribbon, click **Actions > Target Database** or on the status bar, click the database name.

The erwin Data Modeler -- Target Server screen appears.

## Migrating Relational Models to DynamoDB Models



3. In the **Database** drop-down list, select DynamoDB.



4. Click **OK**.

The conversion process starts.


If the erwin Data Modeler dialog box appears, do one of the following:



- Click **Yes** to view the report of unmapped datatypes.
- Click **No** to skip this report.

Once the conversion is complete, the existing model is migrated to DynamoDB model.

## Migrating Relational Models to DynamoDB Models



In the **Objects Count** pane, you can view the details of converted database. The migration process converts and merges multiple tables, columns, and relationships to the DynamoDB format.

## Migration by Deriving a Model

To migrate by deriving a model, follow these steps:


1. Open your relational model in erwin DM.



Ensure that you are in Physical mode.

For example, the following image uses the sample eMovies.erwin model. In the **Objects Count** pane, note the number of tables, columns, and relationships.

## Migrating Relational Models to DynamoDB Models



2. On the ribbon, click **Actions > Design Layers > Derive New Model**.

The Derive Model screen appears. By default, the Source Model is set to your current model.

The screenshot shows the 'Derive Model' dialog box. The 'Select the Target Model' section is active, with the instruction 'Please select the options to create a new derived model'. The 'Compare Level' is set to 'Unknown'. The 'New Model Type' section has three radio buttons: 'Logical', 'Physical', and 'Logical/Physical', with 'Logical/Physical' selected. The 'Create Using Template:' section shows a list with 'Blank Logical/Physical Model' selected. Below this are buttons for 'Remove', 'Browse File System...', and 'Browse Mart...'. A description states: 'Creates a new model with both logical and physical levels (erwin DM classic) and default settings.' The 'Target Database' section has a 'Database' dropdown set to 'SQL Server' and a 'Version' dropdown set to '2019'. At the bottom are buttons for '< Back', 'Next >', 'Derive', 'Close', and 'Help'.


3. In the **Database** drop-down list, select **DynamoDB**.

- Click **Next**.



If the Type Resolution screen appears, click **Finish**.

The Type Selection section appears.




- Select the types of objects that you want to derive into the target DynamoDB model.

- Click **Next**.

The Object Selection section appears. Based on the object types you selected in step 5, it displays a list of objects.


## Migrating Relational Models to DynamoDB Models



7. Select the objects that you want to derive into the target DynamoDB model.


8. Click **Derive**.

The model derivation process starts.



Once the conversion is complete, the existing model is migrated to DynamoDB.

## Migrating Relational Models to DynamoDB Models



In the **Objects Count** pane, you can view the details of converted database. The migration process converts and merges multiple tables, columns, and relationships to the DynamoDB format.



## Couchbase Support

erwin Data Modeler (DM) now supports [Couchbase 7.x](#) as a target database. Apart from the existing objects this implementation supports the following new objects:

- Collection
- Function
- Scope

# Central Scheduler

Starting erwin Data Modeler 12.0, you can now use erwin DM Scheduler to schedule reverse engineering jobs centrally on a local or a remote instance of erwin Data Modeler. You can configure multiple remote machines as servers and set up jobs to run in parallel on these servers. The Central Scheduler saves time and provides you with an improved performance by distributing reverse engineering jobs across multiple servers.

Apart from this, in case of models on erwin Mart, you can now run the Complete Compare process as part of reverse engineering. This enables you to compare the reverse engineering result with the model in your mart. In case of differences, you can save the updates as the latest version of your model in the mart.

The features introduced in this release are:

- [Scheduling Remote Jobs](#)
- [Running Complete Compare](#)
- [Productivity and UI Enhancements](#)

# Scheduling Remote Jobs

You can schedule reverse engineering jobs on a remote server using the scheduler. Before scheduling a remote job, ensure that you configure your remote server.

## Configuring Remote Server

You can set up remote server configurations to schedule a job on the remote server. Configure multiple remote servers, label them, and manage them using the Remote Server Configuration pane.

To schedule a job successfully on a remote server, ensure the following prerequisites are met:



- ◆ Ensure the remote server is running.
- ◆ On the local server, configure the remote server information in the Server Configuration section.
- ◆ Similarly, on the remote server, configure the local server information in the Server Configuration section.

Also, save the server configuration as a predefined configuration for scheduling a job. Access these predefined configurations on the erwin DM Scheduler Event Details page. For more information on scheduling a job using the predefined remote server configurations, refer to [Scheduling Jobs](#) topic.

To create a remote server configuration, follow these steps:

1. On the ribbon, in the Remote group, click **Remote Server Configuration**.  
The Remote Server Configuration pane appears.

Remote Server Configuration

Local Configuration

Server:

Port:





Server Configuration

Server:

Port:



Description:

Label:


 Server	 Port	 Description	 Label

2. On the Remote Server Configuration pane, use the following options in the below table to set up server configurations.

## Scheduling Remote Jobs

Section	Option	Description
Local Configuration	Server	Enter the IP address of the local host.  Displays local host name by default. It is recommended to use the IP address instead of local host name.
	Port	Enter the service port number for the remote scheduler. This field displays the default port number. Click <b>Change</b> to update the port number.
Server Configuration	Server	Enter the IP address of the remote server.
	Port	Enter the port number for remote server.  Ensure the remote server is functional before testing the connection.
	Description	Enter a description for the remote server.
	Label	Select a label color to categorize the server configurations.

- Once you have added remote server configuration, click **Test**.  
The erwin DM Scheduler appears on a successful connection.
- Click **Add**.  
The remote server configuration is added to the list on the Remote Server Configuration pane.




The dialog box is titled "Remote Server Configuration" and contains two main sections: "Local Configuration" and "Server Configuration".





**Local Configuration:**

- Server: Q2P953X233
- Port: 18150
- Change button

**Server Configuration:**

- Server: 192.168.0.184
- Port: 18150
- Test button
- Description: Remote-RE Server
- Label:  Rose

Buttons at the bottom: New, Add, Save, Delete, Import.

 Server	 Port	 Description	 Label
<input checked="" type="checkbox"/> 192.168.0.184	18150	Remote-RE Server	

5. Once you have created a remote server configuration, on the Remote Server Configuration pane, use one of the following options:
  - **New:** Use this option to create a new reverse engineering configuration. Selecting this option resets the Server Configuration section.
  - **Add:** Use this option to add the new configuration. The added configurations are displayed on the configurations list.
  - **Save:** Use this option to save the changes to selected server configuration on the list.
  - **Delete:** Use this option to delete the selected configurations on the list.

## Scheduling Remote Jobs

- **Import:** Use this option to import the configuration from a remote server. Select a server and click **Import**. This option is available when server information is configured under Server Configuration section.



The import replaces the existing server configuration with the latest configuration.


6. Click **OK**.

The remote server configurations are saved as predefined configurations.

When you schedule a job, you can select this configuration under **Predefined List** on the erwin DM Scheduler Event Details page.

Once you have configured the remote server, you can start or stop the remote services. On the ribbon, in the Remote group, click either of the following options:

- **Start Remote Services:** Use this option start a service.
- **Stop Remote Services:** Use this option to stop a service.



### Scheduling Remote Jobs

Before scheduling a remote job, ensure that you start scheduler services and remote services on both, local and the remote instances of erwin DM Scheduler:

- To start a service, on the ribbon, under the Home tab, click **Start Service** option in the Services group.
- To start a remote service, on the ribbon, under the Home tab, click **Start Remote Service** option in the Remote group.

To schedule remote reverse engineering (RE) jobs, do the following:

1. Create an event in one of the following ways:
  - On the ribbon, under the Home tab, click **New**.
  - In the Calendar view, double-click a time slot under the day of your choice.
  - In the Calendar view, right-click a time slot under the day of your choice and click **Add new event**.
2. The erwin DM Scheduler Event Details page appears.



## Scheduling Remote Jobs

3. On the erwin DM Scheduler Event Details page, configure the following options.

Option	Description	Additional Information
Job Name	Specifies the name of the job	
Job Status	Displays the status of the job	
Label	Specifies the color of the job label	
Start Date	Specifies the start date for a job	<ul style="list-style-type: none"> <li>Jobs are run serially. Hence, schedule a reasonable job duration. Ensure that you consider the DB, its size, and the approximate job duration of the current jobs, and then schedule a new job accordingly.</li> <li>Also, in case of multiple jobs sched-</li> </ul>

## Scheduling Remote Jobs

Option	Description	Additional Information
		uled at the same time with the Schedule Now option, it randomly selects a job to run. Therefore, it is recommended that you do not schedule multiple jobs to run at the same time.
Start Time	Specifies the start time for a job	
End Date	Specifies the end date for a job	
End Time	Specifies the end time date for a job	
All day event	Indicates whether it is an all day event	Selecting this option disables the Start Time and End Time options.
Schedule Now	Indicates whether to schedule the job now	Selecting this option disables the Start Time, Start Date, End Time, and End Date options and schedule the job now.
Recurrence	Specifies whether to schedule a job on recurrence bases for the jobs that you do repeatedly. This opens the Scheduling Recurrence page.	To schedule a recurrence job, refer to the <a href="#">Setting Recurrence</a> topic.
Database	Specifies the database for reverse engineering	If you set Redshift as the database, ensure that you do the following:  <ol style="list-style-type: none"><li>1. On the ODBC Data Source Administrator dialog box, go to the <b>System DNS</b> tab.</li><li>2. Select the Redshift data source and</li></ol>

## Scheduling Remote Jobs


Option	Description	Additional Information
		click <b>Configure</b> . The Amazon Redshift ODBC Driver DSN Setup dialog box opens.  3. Under Encrypt Password For, ensure that the <b>All Users of This Machine</b> check box is selected.
Version	Specifies database version for reverse engineering	
Predefined List	Displays a list of pre-defined databases for reverse engineering	
Reverse Engineer	Specifies reverse engineering options for connecting with the selected database. The Reverse Engineering Wizard appears.	On the Reverse Engineering Wizard, click <b>Connections</b> to set up database connections. For more information on database specific connection parameters, refer to the <a href="#">Database Connection Parameters</a> topic.  You can also configure the reverse engineering options available on the wizard. For more information, refer to the <a href="#">Setting Reverse Engineering Options</a> topic.
Remote	Indicates whether to use a remote server for reverse engineering	
Predefined Server Configuration	Displays the lists of pre-defined remote servers for reverse engineering	
Server New		
Port	Specifies the port number	

## Scheduling Remote Jobs

Option	Description	Additional Information
	for the remote server	
Remote Test	Click this option to test the remote server connection	

4. Click **OK**.

Your RE job is scheduled. It runs as configured, and the [job status](#) and its [event log](#) is displayed.




Depending on the settings you make and the job duration that you set, the job tile displays the following information about the job:

- Name
- Status
- Start and end times
- Run time

# Running Complete Compare

The Scheduler tab of the Reverse Engineering Wizard now provides options to run the Complete Compare process when you reverse engineering a model to the mart. This enables you to compare the reverse engineering result with the model in your mart. In case of differences, you can save the updates as the latest version of your model in the mart.



Refer to the following table for option description:

Parameter	Description	Additional Information
Mart Folder	Specifies the location/library in your mart where the reverse engineered model should be saved.	To use this option, ensure that you are connected to a mart. For more information, refer to the <a href="#">Connecting to Mart</a> topic.

## Running Complete Compare

Complete Compare	Specifies whether the Complete Compare (CC) process should run while reverse engineering	
Output File	Specifies the location of the CC output file generated after the reverse engineering process	
File	Specifies that the target model location is on the local system	
Mart	Specifies that the target model location is in the mart	
Using Latest Version	Specifies whether the target model is the latest version of the model in the mart	This option is available only when Mart is selected.
Save To Mart	Specifies whether the reverse engineered model is saved to the mart	This option is available only when Using Latest Version is selected.
Target Model	Specifies the location of the target model for CC	
Option Set	Specifies the option set that must be used for CC	<b>Advanced Default Option Set:</b> Indicates that all erwin DM metadata is included. CC works slowest with this option. <b>Speed Option Set:</b> Indicates that only the essential metadata is included. CC works the fastest with this option set. <b>Standard Default Option Set:</b> Indicates that standard metadata is included. CC works fast with this option set compared to the Advanced option set.

## Productivity and UI Enhancements

Enhancements have been implemented to improve erwin DM Scheduler's productivity and usage experience. These enhancements are:

- [Run Multiple Jobs](#)
- [Predefined Reverse Engineering Configurations](#)

### Run Multiple Jobs

erwin DM Scheduler can now run multiple jobs in parallel on a remote server at the same time.

### Predefined Reverse Engineering Configurations

You can create or import database reverse engineering configurations and use that configuration as a predefined configuration for scheduling a job. Access these predefined list on the erwin DM Scheduler Event Details page.

To create a reverse engineering configuration, follow these steps:

1. On the ribbon, in the Settings group, click **Reverse Engineer Configuration**.  
The Reverse Engineer Configuration List appears.


The screenshot shows a dialog box titled "Reverse Engineer Configuration List" with a close button (X) in the top right corner. The dialog is divided into several sections. The top section, "Reverse Engineer Configuration", contains a "Name:" text box, a "Database:" dropdown menu set to "SQL Server", a "Version:" dropdown menu set to "2012", and a "Reverse Engineer" button. Below this is an "Import" section with an unchecked checkbox, a "Server:" dropdown menu, and an "Import" button. A row of five buttons—"New", "Add", "Save", "Delete", and "Reset"—is positioned below the import section. The main area of the dialog is a table with two columns: "Name" (with a folder icon) and "DB Info" (with a database icon). The table is currently empty. At the bottom center of the dialog is a "Done" button.

2. On the Reverse Engineer Configuration List, use the following options in the below table to create or import configurations.

Option	Description
Name	Enter a name for the configuration.
Database	Select a database for reverse engineering.
Version	Select a database version for reverse engineering.



## Productivity and UI Enhancements

Option	Description
Reverse Engineer	<p>Select this option to specify database options for reverse engineering. The Reverse Engineering Wizard appears.</p> <p>On the Reverse Engineering Wizard, click <b>Connections</b> to set up database connections. For more information on database specific connection parameters, refer to the <a href="#">Database Connection Parameters</a> topic.</p> <div> You can also configure the reverse engineering options available on the wizard. For more information, refer to the <a href="#">Setting Reverse Engineering Options</a> topic.</div>
Import	Select this option to import configurations saved on a remote server.
Server	Select a server on the drop-down, then click <b>Import</b> . The imported configurations are displayed in the configuration list.

- Once you have created a configuration, on the Reverse Engineering Configuration List, use one of the following options:
  - New:** Use this option to create a new reverse engineering configuration. Selecting this option resets the Reverse Engineering Configuration section to add a new one.
  - Add:** Use this option to add the new configuration. The added configurations are displayed in the configurations list.
  - Save:** Use this option to save the changes to a selected configuration on the list.
  - Delete:** Use this option to delete the selected configurations on the list.
  - Reset:** Use this option to reset the data in the Reverse Engineer Configuration section.

- Click **Done**.

The reverse engineering configurations are saved as predefined configurations.

When you schedule a job, you can select this configuration under **Predefined List** on

## Productivity and UI Enhancements

---

the erwin DM Scheduler Event Details page.

The screenshot displays the 'erwin DM Scheduler Event Details' window. It contains several sections for configuring a job:

- Job Information:** Fields for Job Name (job1), Job Status (Error), Label (Sky Blue), and Categories (Red Category).
- Scheduling:** Fields for Start Date (29-09-2021), Start time (10:00:00), End Date (29-09-2021), and End time (10:30:00). It also includes checkboxes for 'All day event' and 'Schedule Now', and a 'Recurrence' button.
- Reverse Engineer:** A section with a 'Reverse Engineer' button and a 'Database' dropdown set to 'PostgreSQL'.
- Version and Predefine List:** A 'Version' dropdown set to '9.6.x/10.x/11.x' and a 'Predefine List' dropdown with 'RE Postgres' selected.
- Remote and Server Configuration:** A 'Remote' checkbox, a 'Predefine Server Configuration' dropdown, and fields for 'Server New' and 'Port'.

## Cassandra: Deriving Models and Advanced Denormalization

You can now perform advanced denormalization when you derive a Cassandra model. This feature provides you with options to do a manual or automatic denormalization.

- Use the auto-denormalization option to merge tables with the target table automatically. This embeds the tables with one-one relationships as User Defined Type and one-to-many relationships as normal columns.
- Use the manual denormalization option to selectively merge columns from source tables to target tables. Further, manual denormalization provides you options to merge multiple columns into single combined column, decide the column embedding type and the embedding process, retain relationships and much more.

### Advanced Denormalization


You can select table and column subsets for denormalizing Cassandra database after deriving a model. Using the Advanced denormalization option, you can merge the source tables and columns with the target based on the requirement.

The denormalization options for Cassandra appear only when the Advanced Denormalization option is selected while deriving a model. Once the model is derived, the Denormalization Wizard for Cassandra model appears and has different sections. By default, Table section is displayed.


To denormalize the model further, follow these steps:

1. On the Tables section, click the **Target** drop-down to select a target table. All the tables will be merged into the target table.


## Cassandra: Deriving Models and Advanced Denormalization




Select **Auto Denormalization** option to merge tables with the target automatically. This embeds the tables in the model with one-one relationships as User Defined Type and one-to-many relationships as normal columns.

Under **Available Tables**, select the that you want to merge. Then, click .

2.




This moves the selected tables under Selected Tables.




3. Click **Next**.


The Column section appears. It displays a list of available columns.



4. Under **Available Columns**, select the that you want to merge. Then, click .



This moves the selected databases under Selected Columns.



Once you have added the selected columns, you can use any of the following:

**New** ()

Use this option to add a new column under Selected Columns.

**Update** ()

Use this option to edit column details such as column name, domain parent, and data type for a selected column.

**Merge** ()

Use this option to merge the selected columns and create a new column under Selected Columns.

### Delete ()

Use this option to delete to the selected columns.

5. Click **Next**.

The Options section appears.

6. Select an **Embedding Type**.

You can select the following embedding options:

- **Embed as Auto:** Use this option to embed tables through an auto-mechanism based on one-to-many and one-to-one relationships.
- **Embed as Normal:** Use this option to embed collections using normal column styles.
- **Embed as UDT:** Use the option to embed collections using a User Defined Type (UDT) styles.

7. Select **Relationships** option to include table relationships to the model.

8. Select **Cascading** options to determine how multiple collections are merged into a single collection.

Use the following cascading options:

- **All:** Use this option to denormalize all relationship levels in a collection into a single collection.
- **Levels:** Use the option to specifies the number of levels up to which collections are denormalized into one collection. For example, if you set Level to 1, all the collections up to level 1 in the relationship hierarchy will be denormalized into a single collection.
- **Auto Cleanup:** Use the option to delete the source collection after denormalization.

Alternatively, click **Commit** to apply changes to the model without exiting the Denormalization Wizard.

9. Click **OK**.

The denormalization process starts and displays collections based on the denormalization option.

## Git Integration

Starting erwin Data Modeler (DM) 12.0, you can connect erwin DM to Git repositories. This allows you to push Forward Engineering (FE) scripts for an Online Mart Model to GitLab or GitHub. Working with these repositories help you in:

- DevOps adoption
- collaborating amongst team members
- version control
- workflow management
- data integrity

To connect erwin DM to Git, ensure that

- erwin DM is connected to erwin Mart Server. To know how to connect erwin DM to erwin Mart Server, refer to the [Connect to Mart](#) topic.
- you have created the required personal access token. To know how to create personal access tokens for GitLab, refer to the GitLab documentation. To know how to create personal access tokens for GitHub, refer to the GitHub documentation.

For information on connecting to Git, refer to the [Connecting to Git Repositories](#) topic.

## Connecting to Git Repositories


Once, you are connected to erwin Mart Server, connect erwin DM to a Git repository. The Git repository may be hosted on GitLab or GitHub.

To connect Git repositories to erwin DM, follow these steps:

1. On the ribbon, click **Mart**.

The available options appear.





2. Click **Connect to Git**.

The Connect to Git page appears.

The image shows the 'Git Connection Manager' dialog box. It has a title bar with a close button. The dialog is divided into two main sections. The top section is titled 'User Credentials' and contains several input fields: 'Connection Name' (a text box with a cursor), 'Git Hosting Service' (a dropdown menu currently showing 'GitHub'), 'User Name' (a text box), 'Password' (a text box), 'Personal Access Token' (a text box), 'Git Repository' (a text box), and 'Git Branch' (a text box). The bottom section is titled 'Recent Connections:' and contains a list box with several empty rows. At the bottom of the dialog are three buttons: 'Save', 'Cancel', and 'Help'.


3. Enter appropriate values in the fields. Refer to the following table for field descriptions.

Field Name	Description	Additional Information
Connection	Specifies the user defined	For example, ConnectGit.

Field Name	Description	Additional Information
Name	connection name	You can create multiple connections each owing to a Git repository.
Git Hosting Service	Specifies the git hosting service to which erwin DM connects	<b>GitLab:</b> Indicates that erwin DM connects to GitLab <b>GitHub:</b> Indicates that erwin DM connects to GitHub
User Name	Specifies the user name to log on to the git hosting service (GitLab or GitHub)	This field is not mandatory.
Password	Specifies the password to log on to the git hosting service	This field is not mandatory.
Personal Access Token	Specifies the personal access token to connect the git hosting service	For example, glpam-A6BFrmClh7o6witzBh_!
GIT Repository	Specifies the URL path of a git repository where you want to push the Forward engineering script	For example, https://-gitlab.com/d4215/GitLabIntegration
GIT Branch	Specifies the branch that is used to push the Forward Engineering script	For example, main.

- Click **Save**.

On successful connection, the connection name appears under Recent Connections.



The image shows a 'Git Connection Manager' dialog box. It has a title bar with a close button. The dialog is divided into two main sections. The top section, 'User Credentials', contains several input fields: 'Connection Name' (text box with 'ConnectGit'), 'Git Hosting Service' (dropdown menu with 'GitLab'), 'User Name' (text box), 'Password' (text box), 'Personal Access Token' (text box with 'glpam-A6BFrmClh7o6witzBh\_'), 'Git Repository' (text box with 'https://gitlab.com/d4215/GitLabIntegration'), and 'Git Branch' (text box with 'main'). The bottom section, 'Recent Connections:', contains a list box with 'ConnectGit' and a scrollbar. At the bottom of the dialog are three buttons: 'Save', 'Cancel', and 'Help'.

Once you are connected to a Git repository, you can [commit FE scripts](#) to a Git repository.

## Committing Forward Engineering Scripts

You can commit Forward Engineering (FE) scripts to a Git repository using:

- **Scenario 1: Committing FE scripts for the first time:**  
Use **Forward Engineer Schema Generation Wizard** wizard to commit a physical database schema or FE script from an Online Mart Model. Ensure that your file names are unique. For more information, refer to the [Scenario 1: Committing FE Scripts for the First Time](#) topic.
- **Scenario 2: Committing alter scripts after making changes to a model:**

Use **Forward Engineer Alter Script Schema Generation Wizard** to commit an alter script after you make changes in the Online Mart Model. You can commit an alter script in two ways:

- **Commit and append an alter script to an existing file in Git repository:** To append the alter script to an existing file, ensure that Auto Append check box is selected and correct File Name and Git Path is set on the Commit to Git page.
- **Commit and create a new alter script file in the Git repository:** To create a new script file clear the Auto Append check box and set the File Name and File Path belonging to an existing file. This creates and commits a new file with the following naming convention: <File Name>\_YYYY-MM-DD\_HH-MM-SS.

For more information, refer to the [Scenario 2: Committing Alter Scripts After Making Changes to a Model](#) topic.


## Scenario 1: Committing FE Scripts for the First Time

With Forward Engineer (FE) Schema Generation Wizard, you can generate a physical database schema or FE script. You can push this FE script for an Online Mart Model to a Git repository. The Git repository may be hosted on GitLab or GitHub. This enables your team to utilize all the advantages of storing a code on a Git repository like efficient collaboration with team members and version control.

To commit FE scripts to Git repositories, follow these steps:

1. On the ribbon, go to **Mart > Open**.


The Open page appears.



2. Click the required model, and then click **Open**.


The Online Mart Model opens.

## Cassandra: Deriving Models and Advanced Denormalization



### 3. Go to **Actions > Schema**.


The **Forward Engineer Schema Generation Wizard** appears.



### 4. On the **Forward Engineer Schema Generation Wizard**, click the **Preview** section.

## Cassandra: Deriving Models and Advanced Denormalization

The FE script appears. For example, in the following image the Preview section displays FE script of a Databricks database. For more information on generating FE scripts, refer to the [Forward Engineering/Schema Generation for Databases](#) topic.



5. Click .

The Commit to Git page appears.

- Enter appropriate values in the fields. Fields marked with an asterisk (\*) are mandatory. Refer to the following table for field descriptions.

Field Name	Description	Additional Information
Connected To	Specifies the connection that connects erwin DM to a Git repository	For example, ConnectGit.
Git Repo	Specifies the Git repository that was set for the connection in the Git Connection Manager	For example, https://-gitlab.com/d4215/GitLabIntegration is set for the ConnectGit connection.  This field autopopulates based on the value set in the Connected To field.
Git Branch	Specifies the Git branch that was set for connection in the Git Connection Manager	For example, main is set for the ConnectGit connection.  This field autopopulates based on the value set in the Connected To field.
File Name	Specifies the user-defined name of the FE script file being committed to a Git repository	For example, Databricks-Sales-Data.sql  Ensure that you use unique file names. If a file name matches with an existing file in the same location




## Cassandra: Deriving Models and Advanced Denormalization

Field Name	Description	Additional Information
Git Path	Specifies the location in the Git repository where the FE script is committed	For example, FY2022/ The FE script is committed to the FY2022 folder inside the root folder of your Git repository.
Commit Summary	Specifies the summary of the push commit	For example, Sales Rectification.
Commit Description	Specifies the description of the push commit	For example, Forward schema script includes December sales data.
Local Path	Specifies the location on your local machine where the FE script is saved	C:\Users\SO\Documents\Databricks

### 7. Click **Commit**.


The FE script file is saved on the local path and committed to the Git repository.

For example, in the following image FE script is committed to a GitLab repository in a file, Databricks-Sales-Data with a commit summary, Sales Rectification is committed using the main branch.




## Cassandra: Deriving Models and Advanced Denormalization

You can click the file to review its content. For example, in the following image, Databricks-Sales-Data's content is visible in a GitLab repository.



You can use FE Schema Generation Wizard to commit FE script using the same connection again. This time the Commit to Git page autopopulates the previously set values in File Name and Git Path.

For example, in the following image File Name is set to Databricks-Sales-Data and Git Path is set to FY2022/.



Committing the FE script again with the same File Name and Git Path overwrites the previous file in the git repository.


## Scenario 2: Committing Alter Scripts After Making Changes to a Model

With Forward Engineer (FE) Alter Schema Generation Wizard, you can generate an alter script for a database after you make changes to a model. You can push this alter script to a Git repository and append it to an existing FE script in the Git repository.

To commit alter scripts to Git repositories, follow these steps:

1. On the ribbon, go to **Mart > Open**


The Open page appears.



2. Click the required model, and then click **Open**.


The Online Mart Model opens.

## Cassandra: Deriving Models and Advanced Denormalization



### 3. Make the required changes in the model.


For example, in the following model, a new table, `cust_dec` with four columns is added.



### 4. Go to **Actions > Alter Script**.

The Forward Engineer Alter Script Schema Generation Wizard appears.


## Cassandra: Deriving Models and Advanced Denormalization



5. On the **Forward Engineer Alter Schema Generation Wizard**, click the **Preview** section.


The alter script appears. For example, in the following image the Preview section displays an alter script of a Databricks database. For more information on generating alter scripts, refer to the [Generating Alter Script for Databases](#) topic.

## Cassandra: Deriving Models and Advanced Denormalization



6. Click .

The Commit to Git page appears. The File Name and Git Path values autopopulates with the values set in the previous commit. You can update the File Name and Git Path as per the requirement.



7. Enter appropriate values in the fields. Fields marked with an asterisk (\*) are mandatory. Refer to the following table for field descriptions.

Field Name	Description	Additional Information
Connected To	Specifies the connection that connects erwin DM to a Git repository	For example, ConnectGit.
Git Repo	Specifies the Git repository that was set for the connection in the Git Connection Manager	For example, https://-gitlab.com/d4215/GitLabIntegration is set for the ConnectGit connection. This field autopopulates based on the value set in the Connected To field.
Git Branch	Specifies the Git branch that was set for connection in the Git Connection Manager	For example, main is set for the ConnectGit connection. This field autopopulates based on the value set in the Connected To field.




Field Name	Description	Additional Information
File Name	Specifies the user-defined name of the FE script file being committed to a Git repository	For example, Databricks-Sales-Data.sql
Git Path	Specifies the location in the Git repository where the FE script is committed	For example, FY2022/ The FE script is committed to the FY2022 folder inside the root folder of your Git repository.
Commit Summary	Specifies the summary of the push commit	For example, Append December Sales.
Commit Description	Specifies the description of the push commit	For example, Forward schema script includes December sales data.
Local Path	Specifies the location on your local machine where the Alter script is saved	C:\Users\SO\Documents\Databricks
Auto Append	Specifies whether the alter script is appended to the file set in File Name and Git Path	By default, the Auto Append check box is selected. To create a new script file, clear the Auto Append check box and set the File Name and File Path belonging to an existing file. A new file with the following naming convention: <File Name>_YYYY-MM-DD_HH-MM-SS is created.  Ensure that you use this check box consistently every time you commit an alter script.

8. Click **Commit**.

The alter script file is saved on the local path and committed to the Git repository.

## Cassandra: Deriving Models and Advanced Denormalization

For example, in the following image an alter script file is committed to a GitLab repository and appended to an existing file, Databricks-Sales-Data with a commit summary, Append December Sales using the main branch.



The screenshot shows the GitLab repository interface for the 'main' branch. The commit summary is 'Append December Sales Data' by a user, authored 8 minutes ago, with a commit hash of 'af7a2c4f'. Below the summary is a table of files in the commit.

Name	Last commit	Last update
..		
.gitkeep	Add new directory	1 week ago
Databricks	Sales Data	1 week ago
Databricks-Sales-Data	Append December Sales Data	8 minutes ago
HumanResourceData	HR Data	1 week ago
PII	Confidential	1 week ago

You can click the file to review its content. For example, in the following image, Databricks-Sales-Data contains the alter script.

## Cassandra: Deriving Models and Advanced Denormalization


---

```
21         status_code string,
22         CUST_number int
23     )
24 USING delta
25 LOCATION 'dbfs:/user/hive/warehouse/erwin.db/cust_credit'
26 TBLPROPERTIES ('delta.minReaderVersion'='1','delta.minWriterVersion'='2');
27
28 CREATE TABLE cust_dec
29 (
30     First_Week BYTE,
31     Second_Week BYTE,
32     Third_Week BYTE,
33     Fourth_Week BYTE
34 );
35
36 CREATE TABLE emp
37 (
38     EMP_first_name string,
39     EMP_address string,
40     EMP_phone int,
41     EMP_address_2 string,
42     email string,
43     salary int,
44     hire_date timestamp,
45     soc_sec_number int,
46     EMP_number string
```

## Oracle: View and Materialized View Enhancement

For Oracle models with views and materialized views that have JOINS, GROUP BY and CTE clauses and/or wildcards, you can now run Reverse Engineering from Script (RES) without hampering the resulting model. Such views and materialized views now result into objects with appropriate columns and relationships with tables.

For complex views and materialized views, use the User Defined SQL tab to view and change a user-provided DDL statement.



### Edit SQL

Select the check box to change the SQL code in the SQL Statement box. Select this check box only if you want the object to contain syntax that erwin Data Modeler cannot represent, for example, a UNION statement. Or Views and Materialized Views

## Oracle: View and Materialized View Enhancement

---

with JOINS, GROUP BY and CTE clauses and/or Wildcards.

When you select this check box, you no longer maintain references to the base tables and columns to which the object refers. After updating the SQL code, click **Commit**.

## Azure Synapse: Table Constraint Enhancement

For Azure Synapse models, you can now process Table Constraints via Reverse Engineering from Script (RES).

# Snowflake Enhancements

erwin Data Modeler (DM) 12.0 brings the following enhancements to the Snowflake database:

- [Object Tagging](#)
- [Reverse Engineering Enhancements](#)
- [Key-Pair Authentication](#)

## Object Tagging

Snowflake implementation in erwin DM now supports object tagging via Tags object for the following objects:

- Table
- Database
- Materialized View
- View
- Role
- User
- Schema
- Warehouse

For more information on object tagging, refer to the [Snowflake Support Summary](#) topic.

## Reverse Engineering Enhancements


Reverse Engineering Wizard now adds filters for objects such as Tables, Views, and Materialized Views in different sections. These sections display all the objects in a schema, without selecting a schema during a JDBC connection.

For more information about reverse engineering a database, refer to the [Selecting the Reverse Engineering Options](#) topic.

To view filters for Tables, Views, and Materialized Views, do the following:

## Snowflake Enhancements

1. On the application ribbon, click **Action > Reverse Engineer**.
2. In the New Model screen, select **Snowflake** as the target server, click **Next**.  
The Reverse Engineering Wizard appears. The wizard now adds filter sections for Tables, Views, and Materialized Views objects. For more information on reverse engineering options, refer to the [Reverse Engineering Options for Snowflake](#) topic.



## Key-Pair Authentication

Snowflake database supports user based key-pair authentication for reverse engineering and forward engineering models. You need a private key, public key, and password to successfully connect to a database using the key pair authentication method.



## Snowflake Enhancements

---

You can use either of the following methods to authenticate the database connection:

- [Authenticate using unencrypted key](#)
- [Authenticate using an encrypted key](#)



To generate a private and public key, ensure that you installed OpenSSL 64 bit version and the set environment variables path in your machine.

### Authentication using Unencrypted Key

To set up a database connection using an unencrypted key, you need to generate a private key and a public key. Then, run the script in the Snowflake console to establish a successful connection.

To authenticate database connection using an unencrypted key, follow these steps:

1. Open Command Prompt, and execute the following command to generate a private key:

```
openssl genrsa 2048 | openssl pkcs8 -topk8 -inform PEM -out  
<private key>.p8 -nocrypt
```

In the above statement replace the <private key> with a relevant file name of the key as shown in the below example:

```
openssl genrsa 2048 | openssl pkcs8 -topk8 -inform PEM -out rsa_key.p8 -nocrypt
```

This generates a private key file (.p8 file format) in the specific folder location.



Ensure that the .p8 file is stored in a folder and specify the file path in the **Private Key File (For Key-Pair)** field while you establish connection during reverse engineering or forward engineering. Specify the file path along with the file name as shown in the example below.

```
C:\Users\<User>\Documents\Keys\rsa_key.p8
```

2. Execute the following command to generate a public key using private key:

```
openssl rsa -in <private key>.p8 -pubout -out <public  
key>.pub
```

## Snowflake Enhancements

In the above statement replace the <private key> and <public key> with a relevant file name as shown in the below example:

```
openssl rsa -in rsa_key.p8 -pubout -out rsa_key.pub
```

This generates the public key file (.pub file format) in the specific folder location.

3. Open the public key file in a notepad and copy the key.
4. Go to Snowflake database console, enter the following command with a user name and a public key (in the following format):


```
alter user <user name> set rsa_public_key='<public key>'
```

In the above statement replace the <server name> and <public key> with relevant parameters as shown in the below example:

```
alter user jsmith set ras_public_key='MIIBIjANBgkqhkiBrChCIKZ2
```

5. Click **Run**.

The statement is executed and the status is displayed.



The screenshot shows the Snowflake database console interface. At the top, there is a 'Run' button and a status bar indicating 'All Queries' and 'Changes not saved'. Below this, the SQL query is displayed: `alter user jsmith set rsa_public_key='MIIBIjANBgkqhkiBrChCIKZ2`. The query is executed, and the results are shown in a table with the following structure:

Row	status
1	Statement executed successfully.

Once the keys are generated, you can enter other database connection parameters to establish a successful connection in erwin DM. For more information about database connection parameters, refer to the [Database Connection Parameters](#) topic.

## Authentication using an Encrypted Key

To set up a database connection using an encrypted key, you need to generate private key, public key and, set an authentication password. This process also involves creating two

## Snowflake Enhancements

---

private keys that are used to setup authentication using an encrypted key. Then, run the script in the Snowflake console to establish a successful connection.

To authenticate database connection using an encrypted key, follow these steps:

1. Open Command Prompt, and execute the following command to generate a private key:

```
openssl genrsa 2048 | openssl pkcs8 -topk8 -inform PEM -out  
<private key>.p8
```

In the above statement replace the <private key> with a relevant file name of the key as shown in the below example:

```
openssl genrsa 2048 | openssl pkcs8 -topk8 -inform PEM -out rsa_key.p8
```

This generates a private key file (.p8 file format) in the specific folder location.

2. Enter a encryption password and verify it.
3. Execute the following command to generate a second private key using the private key in step 1:

```
openssl pkcs8 -topk8 -inform PEM -v1 PBE-MD5-DES -in <private  
key>.p8 -out <private key 2>.p8
```

In the above statement replace the <private key> and <private key 2> with relevant file name of the key as shown in the below example:

```
openssl pkcs8 -topk8 -inform PEM -v1 PBE-MD5-DES -in rsa_key.p8 -out <private key  
rsa_key2.p8
```

This generates a public key file (.pub file format) in the specific folder location.



Ensure that, this .p8 file is stored in a folder and specify the file path in the **Private Key File (For Key-Pair)** field while you establish connection during reverse engineering or forward engineering. Specify the file path along with the file name as shown in the example below.

```
C:\Users\<User>\Documents\Keys\rsa_key.p8
```

4. Enter a pass phrase for the private key.
5. Enter the encryption key and verify it.

## Snowflake Enhancements

6. Execute the following command to generate a public key using the private key in step 3:

```
openssl rsa -in <private key 2>.p8 -pubout -out <public key>.pub
```

In the above statement replace the <private key 2> and <public key 2> with a relevant file name of the key as shown in the below example:

```
openssl rsa -in rsa_key2.p8 -pubout -out rsa_key2.pub
```

This generates the public key file (.pub file format) in the specific folder location.

7. Enter the pass phrase of the second private key in step 4.
8. Open the second public key file in a notepad and copy the key.
9. Go to Snowflake database console, enter the following command with a user name and a public key (in the following format):


```
alter user <user name> set rsa_public_key='<public key>'
```

In the above statement replace the <server name> and <public key> with relevant parameters as shown in the below example:

```
alter user jsmith set ras_public_key='MIIBIjANBgkqhki....'
```

10. Click **Run**.

The statement is executed and the status is displayed.



The screenshot shows the Snowflake database console interface. At the top, there is a 'Run' button and a status bar indicating 'All Queries' and 'Changes not saved'. Below this, the SQL command is entered in the editor: `alter user jsmith set rsa_public_key='MIIBIjANBgkqhkiBrChCIKZ2'`. The command is highlighted in blue. Below the editor, the 'Results' tab is selected, showing a green checkmark, 'Query ID', 'SQL', '87ms', and '1 rows'. A 'Filter result...' input field and 'Download' and 'Copy' buttons are present. The results table has two columns: 'Row' and 'status'. The first row shows '1' and 'Statement executed successfully.'

Row	status
1	Statement executed successfully.

## Snowflake Enhancements

---

Once the keys are generated, you can enter other database connection parameters to establish a successful connection. For more information about database connection parameters, refer to the [Database Connection Parameters](#) topic.

## MongoDB: Schema Validation

erwin Data Modeler 12.0 now supports schema validation for fields in a collection based on the field's data type. The scripts are not generated if the data in the fields are not inline with the assigned data type. If the validations are not met, application displays an error.


Also, you can exclude validations for one or more fields in a table when you generate a script using forward engineering and reverse engineering. This option overrides assigned data type of a field and generates script successfully.

This topic walks you through the steps to exclude schema validations for fields in a simple table (collection) and generate schema using an example. The table below lists the fields and assigned data types in a MongoDB collection, Customer.

Fields	Data Type
Name	STRING
Phone	INTEGER
Address	OBJECT
Street	STRING
City	STRING
Year	INTEGER

The below screenshot displays the fields in a collection along with the assigned data types in the field property editor screen.

## Snowflake Enhancements




To validate The below screenshot displays the fields in a collection along with the assigned data types in the field property editor screen.

This topic walks you through the steps to create associations between environments, business terms, and tables. Then, use the environment as a unique qualifier for association using an example.

## Diagramming: Hide and Unhide Diagram Nodes

For complex models with many nodes in the diagram, the diagram menu provides hide and unhide options. These options enable you to selectively view or hide Entity, View, and Materialized View nodes from the complex and large diagram and focus only on necessary nodes. These options are also accessible via right-clicking the node.



For Neo4j database, you can hide or unhide nodes only in the orthogonal layout. Also, you cannot hide the Supertype or Subtype Entity and isolated nodes.

### To hide or unhide nodes

1. Open the diagram in which you want to hide or unhide nodes.
2. Select one or multiple nodes.
3. On the diagram menu, work with the following available options:

#### Hide

Hides a single or multiple selected nodes in the diagram.


#### Hide Neighborhood

## Diagramming: Hide and Unhide Diagram Nodes

---

Hides a single selected node and all its neighboring nodes in the diagram.

### Unhide

Unhides the neighboring hidden nodes of a single selected node with the visual hiding cue () in the diagram. This option resets the selected objects to their default sizes.

### Unhide All

Unhides all the hidden nodes that the single selected node can reach in the diagram or unhide all the hidden nodes when no node is selected in the diagram.



You can also access these options by right-clicking the nodes.


4. Click Save on the File menu.

Your diagram is saved and can be retained whenever you open a model.



# Data Vault Enhancements

erwin Data Modeler (DM) now supports model-level and table-level rollback function for Data Vault models. To rollback your model or table to its earlier state, open **Model Editor** > **General** tab and clear the **Data Vault 2.0** check box. This restores your model or table to its earlier state.



Additionally, the Data Vault Component Type selector is now available only when the model is configured to be a Data Vault model.

For more information, refer to the [Data Vault](#) topic.

## Productivity and UI Enhancements

Several additions and enhancements have been implemented to improve erwin Data Modeler's (DM) productivity and usage experience. These enhancements are:

- [Copy Neighborhood](#)
- [Object Browser](#)
- [Column Editor Shortcut](#)
- [Graph Display Level](#)
- Denormalization and deriving models now creates new models instead of overwriting source models.
- [Generate diagram picture in multiple formats](#)

### Copy Neighborhood

You can copy neighboring objects of an object in a diagram and paste it to a different model.

#### To copy neighboring objects to a different model

1. Open a diagram and select an object of which you want to copy neighboring objects.
2. In Home menu, click Copy Neighborhood.

The neighboring objects are copied.

3. Open the diagram to which you want to copy the objects.
4. Click Paste.

If none of the neighboring objects exist in the source diagram, the selected object is copied and can be added to new model.

If one or more selected objects exist in the target diagram, a message appears informing you that the objects are pasted as new objects in the model. The new objects follow the naming standards of the model, and are displayed in the same location as in the source diagram. In addition, the new objects appear in the Model Explorer.

## Productivity and UI Enhancements

---

If none of the selected objects exists in the target diagram, the selected objects are only displayed in the diagram. They are not added to the model as new objects.




Cut or copied objects remain on the clipboard even after you paste them into another location. This is convenient if you want to paste more than one copy. But, if you have a large copy selection on the clipboard, it can take up too much memory. To free up memory, after you finish copying and pasting, select an entity and copy it to the clipboard to replace the large copy set.


## Object Browser

- A new tab, <Object> Info has been added for all databases. It displays tables, records, collections, documents, JSON Objects, and nodes, in your model or in the selected object along with the counts based on database. Apart from this, for Couchbase and Neo4j models, database-specific tabs have been added:
  - The Couchbase tab displays global indexes and full text indexes along with their counts.
  - The Neo4j tab displays global indexes and global constraints along with their counts.


## Productivity and UI Enhancements




## Column Editor Shortcut


You can now access the columns of a table via the table editor instead of having to open the column editor explicitly. Use the  icon on the table editor.

## Productivity and UI Enhancements



## Graph Display Level

A new display level, Graph, has been added to facilitate easier switch for graph databases. Derived NoSQL graph models have table-like representation by default. To convert such models to graph-like representation, on the ribbon, go to **View > Display Level** group. Then, click . This converts the model diagram as follows:



## Generate Diagram Picture in Multiple Formats


You can now [generate picture](#) reports of a single or multiple diagrams in one submission in the following formats:

- Enhanced Metafiles (.emf)
- PNG (.png)
- JPG (.jpg)
- SVG (.svg)
- PDF (.pdf)







To generate diagram picture, open a model, go to **Tools > Diagram Picture**. Then, select either of the following option to generate picture:

- Click **Current** to generate a single picture diagram of you current model. For more information, refer to the [Generate Current Diagram Picture](#) topic.
- Click **Selected** to generate multiple diagrams based on your selection. For more information, refer to the [Generate Multiple Diagram Pictures](#) topic.

## Productivity and UI Enhancements



- The [REDB process](#) now stores the database connection parameters, such as DBMS Name/DSN, IP Address/Host Name, and Port under Environment Details in erwin Data Intelligence Suite.

Data Dictionary	Environment Details	Extended Properties	Data Lineage	Impact as Source	Impact as Target	Mindmap
<b>Workflow Status</b>						
System Environment Name*	Demo_SQS2019_REDB_DISV11		Driver Name*			
System Environment Type	erwin DM Mart - SqlServer		DBMS Name/DSN*	disv11		
Data Steward			IP Address/Host Name*	localhost		
Server Platform			Port**			
Server OS Version			User Name*			
File Management Type			Password*			
File Location			Url*			

- You can now run jobs immediately using the [Run Now](#) feature.



**Schedule Job**

CATALOG INFORMATION   DI INFORMATION   **JOB INFORMATION**

Job Name  
TechPubs

Scheduled Job On  
2021/10/10 12:00 AM

Job Interval  
Daily

☐ Notify Me

Notification Email

CC List

☐ Run Now

< PREVIOUS   SUBMIT

- DM Connect for DI has been upgraded to support:
  - all new databases
  - erwin Data Intelligence Suite (DI Suite) v10.2, v11.0, and v11.1

## erwin Mart Server Enhancements

erwin Mart Server has undergone several enhancements as follows:

- You can now test LDAP connections using the erwin Mart Configuration screen.
- Session timeout has been updated to 30 minutes.
- [Special characters](#) support has been updated.
- [Configuration](#) to use IIS and SSL has been updated.

## PostgreSQL Certification

erwin Data Modeler (DM) and erwin Mart Server 12.0 are now certified to work with PostgreSQL versions as follows:

- erwin DM: Versions 9.6.24, 10.20, 11.14, 12.9, and 13.5.
- erwin Mart Server: Versions 9.6.24, 10.20, 11.14, 12.9, 13.5, and 14.1.